Somali Democratic Republic Ministry of Agriculture

Mogambo Irrigation Project

Agricultural Operations and Mechanisation Planning Report

Sir M MacDonald & Partners Limited
Consulting Engineers
Demeter House, Cambridge CB1 2RS, United Kingdom

JUNE 1984

	CONTENTS	Page Nr
SUMMARY		S-1
CHAPTER 1	INTRODUCTION	
	1.1 Present State of Construction 1.2 Scope of the Planning Report 1.3 Review of Existing Agriculture	1-1
CHAPTER 2	AGRICULTURAL OPERATIONS	
	 2.1 Cropping Programme 2.2 Field Operations 2.3 Crop Production Inputs 2.4 Farm Labour 2.5 Hand Tools 2.6 Protective Clothing 	2-1 2-2 2-6 2-6 2-6 2-7
CHAPTER 3	MECHANISATION	
	3.1 Selection of Machine Type an Rice 3.2 Selection of Machine Type an Irrigated Cotton 3.3 Machine Quantification 3.4 Training	3-1
CHAPTER 4	OPERATION AND MAINTENANCE	
	 4.1 Mechanical Plant for Operation Maintenance 4.2 Operation and Maintenance for Administration Buildings and 4.3 Operation and Maintenance for Irrigation and Drainage System 	or Housing, Services 4-8 or the
CHAPTER 5	MANAGEMENT AND STAFFING	
	 5.1 Present Status 5.2 Proposed Organisation and St 5.3 Management Organisation 5.4 Implementation Schedule 	5-1 5-2 5-10 5-10
CHAPTER 6	TRANSPORT	
	6.1 Types of Vehicles6.2 Number of Vehicles6.3 Running Costs	6-1 6-1 6-2
	(1)	

CONTENTS (cont.)

		Page No
CHAPTER 7	MECHANICAL WORKSHOPS AND STORES	
	7.1 General 7.2 Equipment and Tools 7.3 Spare Parts	7-1 7-1 7-2
CHAPTER 8	BUDGET ESTIMATES 1984 to 1986	
	8.1 Basis for the Estimate 8.2 The Budget Estimates	8-1 8-2
APPENDICES		
APPENDIX I	Terms of Reference	I-1
APPENDIX II	Delinting of Cotton Seed	П-1
APPENDIX III	List of Agricultural Equipment and Operations and Maintenance Equipment	ш-1
APPENDIX IV	Detailed Cost Estimates	IV-1

LIST OF FIGURES

Figure Nr		Following Page Nr
2.1	Crop Calendars and Timing of Field Operations	2-2
3.1	Tractor and Combine Harvester Utilisation Chart	3-1
3.2	Tractor Drawn Levelling Frame	3-2
5.1	Proposed Organisational Structure	5-2
5.2	Implementation Schedule	5-12

LIST OF TABLES

Table Nr	Title	Page Nr
2.1	Cropping Programme 1985 to 1986	2-1
2.2	Crop Productions Inputs 1985 and 1986	2-8
2.3	Paddy Rice: Labour Requirements by Field Operation	2-9
2.4	Cotton: Labour Requirements by Field Operation	2-10
3.1	Days Available for Mechanised Operations - Der Season	3-6
3.2	Output of Machinery (Based on 50 Minute Working Hour) 3-7
3.3	Days Available for Individual Land Preparation Operations - Der Season	3-7
3.4	Days Available for Mechanised Operations - Gu Season	3-8
3.5	Days Available for Individual Land Preparation Operations - Gu Season	3-9
3.6	Days Available for Mechanised Operations of the Cotton Crop	3-9
3.7	Number of Machines Required - Rice	3-12
3.8	Number of Machines Required - Cotton	3-13
3.9	Machinery Requirement: 1985 and 1986	3-14
3.10	Total Number of Machine Hours	3-15
41	Vehicles and Plant for Operation and Maintenance	4-2
5.1	Project Staff Requirements : Project Headquarters	5-3
5.2	Definition of Management Units	5-4
5.3	Project Staff Requirements : Field Management	5-5
5.4	Farm Labour Requirements 1985/86	5-7
5.5	Project Staff Requirements : Workshop and Stores	5-8
5.6	Project Staff Requirements : Irrigation Department	5-9
6.1	Estimate of Requirement for Transport	6-1

LIST OF TABLES (cont.)

Table Nr	Title	Market 1	Page Nr
8.1	Cost Estimates 1984	to 1986	8-3
IV.1	Capital Costs - Proj	ect Transport	IV-2
IV.2	Capital Costs - Ope and Equipment	ration and Maintenance Plant	IV-3
IV.3	Capital Costs - Agri	cultural Machinery	· IV-4
IV.4	Capital Costs - Wor Plant and Equipment	kshop and Mechanical Stores,	IV-5
IV.5	Mogambo Headquart	ers - Staff Salaries and Wages	IV-6
IV.6	Workshop and Mecha and Wages	anical Stores - Staff Salaries	IV-7
IV.7	Irrigation Operation	- Staff Salaries and Wages	IV-8
IV.8	Field Management -	Staff Salaries and Wages	IV-9
IV.9	Project Transport -	Fuel, Lubricants and Spare Par	ts IV-10
IV.10(a)	Heavy Plant - Fuel,	Lubricants and Spares	IV-11
IV.10(b)	Heavy Plant - Fuel,	Lubricants and Spares	IV-12
IV.11(a)	Agricultural Machine	ery - Fuel, Lubricants and Spar	es IV-13
IV.11(b)	Agricultural Machine	ery - Fuel, Lubricants and Spar	es IV-14
IV.12	Irrigation and Drains and Spare Parts	age System - Fuel, Lubricants	IV-15
IV.13	Agricultural Labour	Force - Wages	IV-16
IV.14	Housing, Administration of Maint	tion Buildings and Services - enance	IV-17
IV.15	Agricultural Inputs -	Unit Costs	IV-18
IV.16	Agricultural Inputs -	Annual Costs	IV-19
		The state of the s	

SUMMARY

With the construction of the Mogambo Irrigation Project well underway and the Agricultural Management Contract not yet awarded, a detailed planning study of both the agricultural operations and mechanisation required for the project became critical. This report reviews the original proposals contained in the previous studies and makes recommendations on agricultural operations, mechanisation for agriculture and operating and maintenance, transport, workshops, and management and staffing.

Agricultural operations are discussed in Chapter 2. In that section the variety of rice recommended has been changed to varieties IR 24 and IR 22. The quantities of fertiliser and weed control have also been recommended. The application of herbicide has also been altered from the original studies from aerial spraying to the use of tractor-mounted sprayers.

The selection process for each type of machine for both agriculture and operation and maintenance is described in Chapters 3 and 4. The final recommendations in numbers for each item of equipment takes into consideration the common usage of plant between the agricultural and operation and maintenance functions.

The management and staffing requirements are discussed in Chapter 5. For the agricultural organisation it is recommended that the field management is divided into four sections determined by methods of irrigation, independence of irrigation operation and standardising size as far as possible.

Transport and workshop requirements are described in Chapters 6 and 7.

The total budget requirements until the project has reached full development at the end of 1986 are summarised in Chapter 8 with the detailed make-up covered in the appendices.

CHAPTER 1

INTRODUCTION

L1 Present State of Construction

Construction of the Mogambo Irrigation Project (MIP) is now well underway. The first major construction contract (M1) for project buildings including houses, offices, workshops and stores, etc. is expected to be complete by mid-1984. The contractor for the land development, irrigation and civil works contract (M2) is due to commence work on site early in March 1984. Although this represents a delay of approximately four months from the original planning it is still expected that:

- 459 ha of surface irrigated land will be developed and available for cultivation in the 1985 gu season;
- 1 134 ha of surface irrigated land and 122 ha of sprinkler irrigated land will be available for cultivation in the 1985 der season;
- full development of Phase I (2 052 ha under surface irrigation and 163 ha under sprinkler irrigation) will be completed in time to allow cultivation of the entire area during the 1986 gu season.

Although the planning is based on the above figures it should be recognised that this is totally dependent on the contractor's performance. In the event that water will not be available for the gu season in 1985 the initial 459 ha of surface irrigated land may not be developed.

L2 Scope of the Planning Report

With less than a year before agricultural operations are due to start, it is essential that detailed planning of these operations is commenced. The purpose of this study therefore is to carry out the detailed planning necessary to facilitate implementation of the agricultural programme; firstly by defining precisely what the programme will involve and secondly by specifying the machinery, agricultural inputs, labour and operating budget necessary to implement the programme successfully. Specifications for machinery and equipment will be in such detail as to allow procurement to proceed immediately.

The rice mill due to be constructed by the beginning of 1986 is a discrete and independent entity not considered within the scope of this report. Similarly, budget costs for the Rice Mill will be provided at a later stage.

The Terms of Reference relating to this Report are included in Appendix I.

L3 Review of Existing Agricultural Proposals

The agricultural proposals to be implemented are contained in the report on the Mogambo Irrigation Project: Additional Study for an Alternative Development (Sir M. MacDonald & Partners Ltd., March 1980). They are supported by Annex 3 (Agriculture) of the Supplementary Feasibility Study Report (Sir M. MacDonald & Partners Ltd., August 1979). The initial phase of the project is designed primarily for the production of basin irrigated rice

(2 052 ha) with a small adjoining area (163 ha) of sprinkler irrigated cotton. Both production systems are dependent upon intensive mechanisation from land preparation through to harvesting and trash disposal. However, whereas the rice will be mechanically cropped the cotton will be hand picked.

Since the aim of this study is to complete the detailed planning necessary to implement the original concept, there is no question of the basic cropping pattern or production system being altered significantly. Within this study it has been necessary to reconsider the following aspects; the varieties of rice to be grown; the cropping intensity and distribution of cropping between the gu and der seasons and the application of herbicides. The main reason for this is the knowledge gained at the Fanoole and Barro Uen State Farms since the Supplementary Feasibility Study and the Alternative Development Study were completed. Although the area cultivated on either farm has never exceeded 200 ha in a single season, considerable rice growing experience has been accumulated and it is intended that the benefits of this experience are reflected in the detailed planning for MIP.

(a) Rice Varieties

In the 1979/80 studies a short season variety Vista (105 days to maturity) which had been tried successfully at Afgooye and which was equally well suited to basin and upland conditions, was proposed. Its principal advantage lay in its short season characteristic, which would enable a relatively high cropping intensity of 150% to be achieved. Its main disadvantages, however, were susceptibility to bird damage and proneness to shattering. It is no longer grown commercially in Somalia.

At Fanoole and Barro Uen, two varieties IR 24 and IR 22 respectively are grown. Both are potentially higher yielding and less prone to shattering or bird damage. They are long grained translucent varieties and acceptable for consumption by the Somali people. Although both varieties are longer season (120 to 125 days) than Vista, with good management it should still be possible to achieve 150% cropping intensity in one year. As IR 22 is sensitive to photoperiod it should be limited to the der season when less cloud is expected during the growing season. IR 24 is not sensitive to photoperiod and can be used for either season.

(b) Cropping Intensity

In the Alternative Development Study a cropping intensity of 150%, 75% in each season, was proposed. Whilst 150% intensity per annum is considered attainable, a rigid adherence to 75% intensity in each season may not be practical in the years when either high rainfall or low river flow is encountered in April.

The implications of this is that each year will have to be taken individually, and whilst a cropping intensity of 150% per annum remains the target, the intensity in each season will vary according to the conditions prevailing at the time. On the basis of the existing data, however, it is quite likely that the April rains may restrict the gu season cropping intensity to less than 75% but the shortfall would be made up in the following der. However, whilst the design capacity of the irrigation system can easily accommodate 100% intensity in the gu season because the crop water requirements are lower at this time, the higher der season requirements for 100% intensity can nearly be met by the system.

(c) Field Operations

The production system is based on intensive mechanisation of almost all field operations. This was proposed in 1979 primarily because of a shortage of labour, and mechanisation represented the best means of achieving a high cropping intensity, timely operations and high yields. Since then labour availability has not improved; if anything, competition for labour in the Lower Juba has increased markedly due to the expansion of the Juba Sugar Company, rehabilitation of banana plantations, and a further planned expansion in the banana hectarage of around 2 000 ha. There is, therefore, no reason to change the production system to one which is more dependent upon labour intensive methods, and consequently the operations planned in the following chapters are largely similar to those outlined in the Supplementary Feasibility Study and Alternative Development Reports.

The only operation which differs from the early proposals is the application of herbicides. Originally when the planning was carried out for the ultimate development of 6 400 ha, it was assumed that aerial application of herbicides on rice, aerial top dressing of nitrogen and aerial spraying of pesticides on cotton represented the cheapest and most effective means of application. With the reduced scale of the Phase I operations, aerial application of rice herbicides can no longer be justified for Mogambo alone. The Phase I rice area would require a total of 4 to 6 days actual spraying time. Since planting and germination extends over a 40 to 45 day period, the diseconomies of bringing an aircraft into the country on a number of occasions, or of maintaining an aircraft in the country for a 40 to 45 day period would be prohibitive. Furthermore, an airstrip would have to be cleared and prepared within the project area. The strip would have to be a minimum of 800 m long and 30 m wide with a central strip 3 m wide surfaced with crushed coral. At present there is no provision for this in Phase I of the project, but there is an existing airstrip at the Juba Sugar Project, 35 km away, which could be considered for use in the spraying operation, especially in association with the Fanoole Project. Taking these facts into consideration aerial spraying of rice herbicides is not considered appropriate and the use of tractor mounted sprayers is now proposed. Tractor mounted sprayers are already being used at Fanoole and Barro Uen State Farms and although there are certain disadvantages this method has proved reasonably successful. The disadvantages are: less timely application in that spraying by tractor would almost certainly mean a delay in spraying of 3 to 5 days compared with aerial application; slightly higher rates of application may have to be used and control of weeds would generally be less effective. Provision for spot spraying of weeds which have survived would have to be made. The spraying operations will be much more susceptible to the incidence of rainfall.

Although aerial spraying is not economic for Mogambo Phase I alone, it should be reconsidered for any further phases and the potential for collaboration with Fanoole should be reviewed as the area of rice develops at both projects.

CHAPTER 2

AGRICULTURAL OPERATIONS

2.1 Cropping Programme

The cropping pattern is not complex and is based on mono-cropping rice on the surface irrigated area at an annual intensity of 150% with some flexibility over the distribution of intensity between the gu and der seasons. Initially, the sprinkler irrigated land will be devoted to mono-cropping cotton grown under a conventional wide row system in the der season. The aim will be to test the feasibility of cotton growing and eventually to investigate the potential for cultivation of a narrow-row system suitable for mechanised stripper picking. Whilst the potential for cotton cultivation will be examined in the first two years, the possibility for a rotation incorporating upland rice and maize in the longer term should not be ruled out.

The cropping programme for the first two years during the construction period to full development is summarised in Table 2.1.

TABLE 2.1 Cropping Programme 1985 to 1986

		19	985		1986
		gu (ha)	der (ha)	gu (ha)	der (ha)
Available land:	Surface irrigation	459	1 134	2 052	2 052
	Sprinkler irrigation	122	122	163	163
Cropping program	me : Paddy rice	459	900	1 539	1 539
	Cotton		122		. 163

In the 1985 der season it is anticipated that 900 ha of rice is the maximum that can be expected. This will comprise the incremental area of 675 ha to be developed in time for planting during the 1985 der season with approximately half of the area cultivated during the preceding gu season. The final cropping plan of 3 078 ha of rice per annum should be achieved from 1986 onwards. For the cotton crop, 122 ha of sprinkler irrigated land will be available for cultivation in 1985 and 163 ha in 1986. Although this crop will initially be restricted to the der season, ultimately the establishment of a rotation comprising cotton, maize and upland rice should not be ruled out. This possibility should be further considered by the management team to implement at a later stage.

2.2 Field Operations

The cropping programme for basin irrigated rice and sprinkler irrigated cotton is illustrated in Figure 2.1. Husbandry practices and the required levels of inputs to be used are described in the following sections. Detailed discussion of the mechanised operations and machinery selection is contained in Chapter 3.

2.2.1 Basin Irrigation Rice

(a) Land Preparation

Land preparation will involve primary and secondary cultivation to depths of 200 mm and 150 mm respectively, using heavy disc harrows followed by levelling. These operations will be carried out between mid-December and mid-April for the gu season crop and from July to the end of September for the der season crop.

(b) Rice Varieties

Varieties IR 24 and IR 22 are currently grown in Somalia and seed is available from the Fanoole and Barro Uen State Farms. As both have a high yield potential, largely free from major pest and disease problems and are acceptable to the Somali consumer, there is no need to look for alternatives at this stage. IR 24 should be grown in the gu season and IR 24 or IR 22 grown in the der. IR 22 is not recommended for the gu season because of its sensitivity to photoperiod. The greater incidence of cloud cover in the gu would prolong its period to maturity.


(c) Planting

Rice will be drilled into a dry seedbed at a seed rate of 140 kg per ha. This is higher than normal but is considered necessary because of seed losses to birds. At Fanoole the seed rate is 180 kg per ha while at Barro Uen rates of between 150 and 180 kg of seed are used. As the seed will be covered by harrowing immediately after planting, it is expected that losses to birds will be considerably reduced and a seed rate of 140 kg per ha will produce a satisfactory stand.

Planting of the gu crop will take place between the middle of March and the end of April. Planting in March will involve an element of risk in that germination could be initiated by early rains which do not sustain the crop until there is adequate water in the Juba River for irrigation. This risk however, is unavoidable, as the ability to get into the basins later to cultivate and plant could be limited by heavy rains. When conditions are too wet for drilling, broadcasting the seed by spinner may still be possible and would be tried. Ideally a significant proportion of the area could be planted before the rains and a controlled programme of germination by irrigation followed as river water becomes available as each gu season will vary and management planning will have to be flexible to cover any eventuality.

The der crop will be planted during August and September. The low rainfall and the reasonably reliable river flow in these months should allow a planned and controlled programme of planting and germination. Overall the der crop should present considerably fewer difficulties than the gu.

Crop Calandars and Timing of Field Operations



(d) Germination

The basins will be irrigated as soon as possible after planting to germinate the crop. If irrigation is completed quickly and the basins are free from standing surface water within 24 hours of commencement of irrigation, this will ensure the best method of even germination and sustained growth of seedlings for the three weeks before the application of herbicides and flooding of the basins is carried out. Pre-irrigation for germination is not recommended because fields would have to be dried out to allow planting. Therefore germination is likely to be uneven and further irrigation following emergence of seedlings would delay application of herbicides due to wet ground conditions in the basins. In the gu season, because of the potential low river flows, pre-irrigation could not be carried out until mid-April, by which time the gu rains are generally at their peak.

With the proposed system of planting into a dry seedbed, the importance of ensuring that basins are free from surface water within 24 hours of irrigation to allow germination, cannot be overemphasised. Rice does not germinate in anaerobic conditions and where pools of water are allowed to remain germination will be poor.

(c) Fertilisers

Since the response of rice to fertiliser levels will be established with experience, the initial levels proposed are based on the consultant's experience taking into consideration the present practices at Fanoole and Barro Uen. Present policy at Fanoole is to apply:

- 150 kg DAP at planting;
- 100 kg urea 15 days after emergence;
- 150 to 225 kg urea at tillering.

At Barro Uen 45 kg DAP and 180 kg urea are applied. This is less than at Fanoole but probably reflects constraints of availability rather than an optimum level.

The following fertiliser policy is proposed for the Mogambo Irrigation Project:

- 150 kg urea per ha broadcast before planting;
- 75 kg DAP per ha combine drilled at planting;
- 100 kg urea per ha hand broadcast at tillering.

Tillering is normally encouraged by reducing the water levels in the basins and this is the most appropriate time for hand broadcasting of the urea top dressing.

(f) Weed Control

A post-emergence application of Stam F34 (Propanil) at a rate of 10 litres per ha will be the main means of weed control. This will be applied by a tractor mounted sprayer approximately 20 days after the initial irrigation to germinate the crop. Ideally the herbicide should be applied when weeds are at the 2-leaf stage, which is normally 16 to 18 days after germination, but 20 days is probably the earliest time when ground conditions will permit access into the basins with the wheeled tractors.

Besides the initial post-emergence spray, spot spraying of weeds will also be necessary. This will be done by hand using knapsack sprayers and for this a requirement of 2 litres per ha of Stam is estimated.

Other herbicides should be tried, either individually or in combination with Stam, at an early stage in the project. These include:

- Avirosan 500 EC (400 Piperophos/100 Dimetha-metryn) as a preemergent spray at a rate of 5 litres per ha). This herbicide is currently used extensively in rice cultivation in Tanzania.
- A combination of 0.5 litres 2,4D amine and 10 litres Stam per ha.
 The addition of 2,4D is reputed to increase the effectiveness of Stam.

Provision has been made in the estimates of inputs required in 1985 and 1986 to enable a trial area of around 100 ha of rice in each season to be treated with Avirosan 500 EC. A much smaller trial of 20 ha to be treated using 2,40 amine and Stam is also recommended.

(g) Pests and Diseases

Both the Fancole and Barro Uen State Farms report that there are no major disease problems, and apart from birds, mainly (Qualea spp), there are no major pests. The birds however, create a very serious problem, by either causing losses in yield or incurring high labour costs for bird scarers. A national Qualea control project, supported by the German Government, is currently being established and it is hoped that some benefits in terms of protection or control may accrue. Nevertheless this problem should receive the immediate attention of the management team as soon as it is established in the field.

(h) Harvesting

Harvesting will be mechanised using combine harvesters. The gu season crop will be harvested between mid-August and the end of September and the der season crop from early December until the first week in February. Grain handling cleaning, and drying should not present any problem from the 1986 der season onwards when construction of the drying and storage complex will be complete. For the 1986 season's harvest, arrangements will be somewhat makeshift but will probably involve sun drying and speedy disposal to Agricultural Development Corporation.

(i) Straw Disposal

Rice straw will be disposed of in a number of ways. Following the der harvest there will be adequate opportunity for drying off and burning. Following the gu harvest there may be instances when burning is not possible because of rainfall and high humidities. In these cases straw would be chopped up using a rotary slasher and then ploughed in.

2.2.2 Sprinkler Irrigated Cotton

The area of cotton cultivated in Somalia has declined since the Supplementary Feasibility Study was completed. There is no irrigated cotton being grown at present, and although the Government is considering rehabilitating the Jamama ginnery, it is not at present operating. The Mogambo cotton crop will therefore have to be ginned at the Somaltex ginnery at Balad. Somaltex, however, is prepared to transport seed cotton to the Lower Juba.

(a) Land Preparation

This will be similar to that for rice and will comprise primary and secondary cultivations to depths of 200 mm and 150 mm respectively, using heavy disc harrows. Annual landplaning or smoothing operations are not considered necessary. Primary cultivation would be carried out during February and March and the secondary cultivation from June through to August.

(b) Varieties

Acala 4.42 is well suited to Somali conditions and meets the requirements of the Somaltex factory at Balad. Somaltex provides undelinted Acala 4.42 seed to growers free of charge. To allow mechanical planting, the seed will have to be delinted on the project. This should not cause serious problems as various well tried and relatively inexpensive methods of acid delinting of small quantities of cotton seed are available. This is detailed in Appendix 2.

(c) Planting

The cotton seed will be planted mechanically in rows 75 cm apart with 20 cm spacing within the row, giving a plant population of around 65 000 plants per ha. The seed rate, using acid delinted seed will be 10 to 12 kg per ha. The seed will be dressed with Fernasan D at a rate of approximately 0.3 kg Fernasan D per kg of seed and the crop will be planted during August.

(d) Fertilisers

As no new data are available on responses to fertilisers in Mogambo the recommendations contained in the Feasibility Study are adhered to. These are 170 kg of urea per ha will be broadcast by spinner prior to final disc harrowing, and 50 kg of DAP will be applied at the planting stage.

. (e) Weed Control

Weed control will be maintained primarily by a combination of herbicides and mechanical cultivation supplemented where necessary by hand weeding.

The herbicide application will comprise a pre-emergence application incorporated in the soil prior to planting. The two most suitable herbicides are Treflan (Trifluralin) or Cotoran (Fluometuran). The choice however, depends upon the weed spectrum in that Treflan provides good control of annual grasses while Cotoran will control annual broad leaved weeds. Cotoran is granular, mixes easily with urea and would be applied with urea prior to final discing. On balance annual grasses are expected to present the most serious problem and initially Treflan, applied before final disc harrowing at a rate of 2.8 l/ha, is recommended. Further experiments should be instituted at an early stage. To facilitate this, provision for purchase of Cotoran, applied at a rate of 5 litres per ha, and Codal 400 EC, which provides control over grasses, applied at a rate of 61 litres per ha, has been allowed in the input estimates.

(f) Pest Control

Insect pests, boll worms, leaf eaters, jassids, aphids and cotton stainers are expected to present serious problems. Control measures will be those recommended in the Feasibility Study and will comprise systematic blanket spraying at 8 to 10 day intervals from first bud formation (i.e. about 40 days after planting) through to 130 days after planting. Nine ULV sprays at a rate of 2.5 l/ha of Nuvacron Combi (Monocrotophos/DDT) will be applied.

(g) Harvesting

The crop will be hand picked in either two or three picks from mid-December through to the end of February. Seed cotton will be collected in heaps in the field and eventually transferred to sacks provided by Somaltex. Somaltex will collect the bagged seed cotton in the field and transport it to the ginnery at Balad.

(h) Trash Disposal

Cotton stalks which have not been collected by villagers for fuel will be chopped by flail chopper and raked into heaps for burning. Any remaining residues will be buried during primary cultivation.

2.3 Crop Production Inputs

The estimated requirements for seed, fertilisers, agrochemicals and sacking or packaging materials are summarised by crop season in Table 2.2. ULV sprayers and their requirements for batteries are discussed in Chapter 3 along with mechanisation. Hand tools for farm labourers are discussed in Section 2.5 of this chapter.

2.4 Farm Labour

This section is concerned solely with the unskilled labour necessary to carry out the field operations (i.e. planting, irrigating, bund and in-field channel maintenance, fertilising, spraying, trash disposal and crop handling, between field and storage, etc.) described in the foregoing sections. It does not therefore, include labour associated with general maintenance of Headquarters' buildings and civil irrigation works or unskilled labour in stores or workshops. These are discussed in Chapters 3, 4 and 7.

Tables 2.3 and 2.4 summarise the labour requirements for rice and cotton respectively by field operation on a man days/ha basis. The tables also illustrate the distribution of the labour requirements throughout the year. Table 2.3 includes a labour allowance for bird scaring. This function will be performed by casual labour, probably women and children, and the numbers will be highly variable from year to year.

Similarly the labour requirement for cotton picking will be variable, being dependent upon the annual cotton yield. In Table 24 the labour requirement has been specified independently and included as casual labour.

2.5 Hand Tools

The farm field labour force has been estimated on the basis of the crop labour requirements in Tables 2.3 and 2.4. The main hand tools required by this labour force are spades, jambis and pangas. Since a labourer will not require all three tools, the maximum number required for each is assumed to be equivalent to 60% of the labour force. The numbers to be procured are thus:

	1985	1986
Number of each tool required	110	180
Number of each tool to be procured	110	70

2.6 Protective Clothing

Protective clothing will be required by labourers assisting with spraying operations in rice and cotton. This includes the gangs using knapsack sprayers for spot herbicide sprays in rice, ULV sprayers for pesticide application in cotton, and those labourers assisting with handling sprays and filling tractor mounted sprayers. Altogether it is estimated that 50 complete sets of tools, leggings, jackets, hats and goggles will be required over the first two years.

TABLE 2.2 Crop Production Inputs 1985 and 1986

	Gu 19	985 Der	Gu	1986 Der
Cropping Programme:	2000	HARRY	9024	
Rice (ha) Cotton (ha)	459	900 122	1 539	1 539 163
Rice Inputs:				
Seed: IR 24 (tonnes) IR 22 (tonnes) Urea (tonnes) DA (tonnes) Stam F 34 (litres) Avirosan 500 EC (litres) 24D Amine (litres) Sacks (number)	65 115 35 5 500 500 10 12 800	65 65 225 70 10 800 500 10 18 500	220 385 120 18 500 500 10 36 500	110 110 385 120 18 500 500 10 36 500
Cotton Inputs:	_	manner:::		
Seed: (undelinted) quintal Sulphuric acid (litres) Fernasan D (kg) Urea (tonnes) DAP (tonnes) Treflan (litres) Cotoran (litres) Codol (litres) Nuvacron Combi (litres)		40 400 450 21 6.5 350 25 30 2 750		50 500 580 28 8.0 460 25 30 3 670

Paddy Rice: Labour Requirement by Field Operation (man days/ha)

Total	4.0 0.2 0.4 0.4 1.0	3.0	23.0	45.0		4.0	0,4	12.0	3.0	23.0	45.0
Feb								2	0.4	1.9	20.0
Jan							,	2.0	0.4	3.2	20.0
Dec							Ċ	2.5	0.4	3.3	5.0
Nov						0.5	0.2	u.> 2.5	0.4	3.9	
Oct						1.0	0.2	2.5	0.4	4.3	
Sep		1.5 0.4	1.9	20.0	5	1.0	0.2	2.5	0.4	4.2	
.h Aug	0.3	0.4	3.2	20.0		0.5	3		0.4	0.7 1.0	
Month Jul Aug	0.4	0.4	3.3	5.0		0.5			0.2	0.7	
Jun	0.5 0.2 0.3 2.5	0.4	3.9			0.5				0.5	
Мау	1.0 0.2 0.2 2.5	0.4	4.3								
Apr	1.0 0.1 0.2	0.4	4.2								
Feb Mar	0.5	0.4	1.0								
	0.5	0.2	0.7								
Jan	0.5		0.5								
Operation	Gu season crop: Bund and irrigation channel maintenance Planting Spraying (herbicide) Spot spraying (herbicide) Top dressing	Crop handling Miscellaneous	Total base labour	Estimated labour for bird scaring	Der season croo :	Bund irrigation channel maintenance	Planting Spraying (herbicide) Soot spraying (herbicide)	Top dressing Irrigating	Crop handling Miscellaneous	Total base labour	Estimated labour for bird scaring

TABLE 2.4
Cotton: Labour Requirement by Field Operation (man days/ha)

Operation					Month	4				- 18	Total
6	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar	
General field maintenance	0.2	0.2	5	0.3							1.0
Planting			0.2								0.2
Fertiliser application			0.2							- 21	0.2
Herbicide application			3								0.3
Spot weeding					TO	1.0	7.0				3.0
Irrigating			1.0	2.0	20	2.0	2.0	7.0			10.0
Pest control				0.5	1.5	12	0.5				4.0
Seed cotton handling & bagging							0.5	1.0	0.5	t	2.0
Trash burning									120	2.0	3.0
Miscellaneous		63	97	0.4			0.4	0.4	0.4		2.3
Total base labour	0.2	0.5	24	3.2	4.5	4.4	2.4	179	2.0		26.0
Picking 1985							12	20	10		400
1986							12	2	13		55.0
1987							17	9	18		75.0

CHAPTER 3

MECHANISATION

3.1 Selection of Machine Type and Size - Rice

A brief description of the selection process for each type and capacity of machine is given in the following sections.

3.1.1 Tractor Type and Size

From Figures 2.1 and 3.1 it can be observed that there is considerable overlap between tillage operations and other operations such as drilling and harvesting. The selection of tractor type need not, therefore, be made on the basis of a general purpose machine suitable for all operations. Two types of tractor; one suited to tillage and another suited for the transport, spraying and drilling operations have been selected. Restricting the types of tractor to two reduces the problems associated with maintenance and ordering and storage of spare parts.

For tillage a direct drive crawler tractor has been selected. The reasons for this are:

- Crawler tractors are able to work in a greater range of soil conditions than wheeled tractors.
- Operation of a crawler tractor and the setting of discs for tillage does not require such a high level of skill from the operator.
- In the soil conditions on the project area, track life is expected to be very high. At the Juba Sugar Project crawlers have worked for over 6 years without any track component replacement.
- At low tillage speeds, crawler tractors have more usable horsepower at the drawbar than wheeled tractors which rely on relatively high speeds to make full use of their horsepower.
- Crawler tractors will be able to cross channels and bunds more easily and with less damage than wheeled tractors. This is particularly so if soil conditions are wet.
- Crawler tractors can be fitted with bulldozer blades for field and road maintenance work. They are also capable of machine and vehicle recovery work. Two crawler tractors should be equipped with angle blades.
- In the conditions expected at the project area, the economic life of the crawler tractors is expected to be twice that of the wheeled tractors. It is anticipated that although the capital costs will be higher per machine the operating costs per ha will be similar if not lower than a wheeled tractor.

For general purpose duties a 75 hp wheeled tractor has been selected. This size of tractor is capable of efficiently carrying out drilling, spraying and general transport work. In order to facilitate easy entry and exit to fields some of the units should be fitted with front wheel drive assist (unequal wheel 4 wheel drive).

3.1.2 Primary Tillage

The main requirements from the primary tillage implement are :

- Penetrate to a depth of approximately 150 mm.
- Cutting and mixing crop residues (rice straw).
- Minimal disturbance of field levels.
- Ability to penetrate hard dry soil conditions if necessary.
- Easy to set and operate.
- Robust, with a low maintenance requirement of the wearing parts.

The implement that best meets these requirements is the heavy ploughing offset disc harrow. When fitted with 760 to 810 mm diameter cut-away discs and with a weight per disc of 200 kg, this implement is capable of cutting up all surface trash and penetrating even in the driest conditions to at least 150 mm in one pass.

Other primary tiliage implements have major drawbacks: disc and mouldboard ploughs are slow, difficult to set and upset field levels; chisel ploughs, although probably best at maintaining levels, are not able to handle large quantities of surface trash. The chisel ploughs also tend to pull dry soil up into large clods which are difficult to break down with subsequent secondary tiliage operations.

3.1.3 Secondary Tillage

Offset disc harrows with smaller discs of 660 mm diameter have been selected for secondary tillage. They will further cut and mix the crop residues and produce a level seedbed. Two passes will normally be required.


3.1.4 Levelling

Using disc harrows for tillage the only areas where upsets in bed level are likely to occur are at the headlands where machines turn. For this reason a quick levelling is required after the tillage operations. The simplest and cheapest way of achieving this is to make a rectangular frame from heavy steel rectangular hollow sections which is then dragged behind a tractor. This is illustrated in Figure 3.2. During the initial years there will be considerable settling of the areas of fill in the basins and frequent levelling of the basins will probably have to be carried out. For this, a tractor drawn scraper plane will be required. Any extreme level differences which cannot be adequately handled by the scraper plane will be levelled using the project grader.

Tractor and Combine Harvester Utilisation Chart

	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NON	DEC	
CRAWLER TRACTOR	e e	3 3 3 Tillag	e - coffon	n n	7111age	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	د و	υ - υ -	. Ø	C C	C C	e .	6
WHEEL TRACTORS	Grain Transport	Ferral Reserved From 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Cutting 1 2 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	1 Drill 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		Post-emer		Spray	ray ray ray 2 2 2 2 2 2 2 2 2 2 2 2 2 Tractors 2 Tractors 2 Tractors 2 Tractors 2 Tractors	Requi	Transport Transport Tractor Tractor Required	
TRACTORS REQUIRED	7777	8	5 5 10 7	6 6 9	4		4	71 21 01 01	16 16 16	8		^	7
COMBINE HARVESTERS	7 7 7 7	-							,,,,				

Figure 3.2
Tractor Drawn Levelling Frame



3.1.5 Seed Drilling

A combination seed/fertiliser drill will be used for sowing. The 75 hp tractors will be able to pull a 21 row machine with 175 mm row spacing, which will give an effective working width of 3.6 m. Spike tooth harrows will be attached behind the drill to cover the seed. Double disc openers to cut through residual surface crop residues will be required, as well as special fluted seed metering rollers to cope with the natural abrasiveness of rice seed.

3.1.6 Spraying

Spraying of herbicides with Propanil will take place when the weeds have reached the two leaf stage. This will occur some 10 to 22 days after the beds have received the first irrigated water to induce germination.

The actual timing of post-emergence herbicide application will be dependent upon weather conditions particularly as the incidence and intensity of rainfall. It is anticipated however, that the majority of the area will be sprayed within the optimum dates. The gu season, because of April rainfall, may present some difficulties and consequently it is proposed to include in addition to conventional tractor mounted sprayers, a self-propelled specialist spraying vehicle which is designed to exert extremely low ground pressures of less than 0.1 kg/sq.cm. Whilst this vehicle will be purchased essentially for evaluation purposes it should provide some flexibility in terms of the conditions under which spraying can take place. Pre-emergence spraying is also a possibility and provision has been made for this.

In addition, knapsack sprayers will be required for spot treatment of weeds which have not been controlled by initial post-emergence sprays.

3.1.7 Harvesting

It is proposed to use a 110 to 125 hp rice combine harvester with a 4.2 m width of cut. In a 5 t/ha crop, gross output will be about 5 t/h. The combine will be fitted with a rasp bar threshing cylinder and concave. Each combine will be supplied with track laying undercarriage attachment as well as the wide profile, low ground pressure wheels and rice tyres. All ground conditions can then be tackled by the combine harvesters.

3.1.8 Transport

Two types of trailer will be required for the project: a flat bed 5 t 4 wheel trailer for transporting seeds and fertiliser to the field; and a 7 t weight transfer, tipping grain trailer. Two different types are required because the seed and fertiliser trailer will need to be easily hitched and unhitched at the ends of fields, whereas the weight transfer trailer will allow the maximum use of tractor capacity in transporting grain to the mill.

3.1.9 Miscellaneous Machines and Implements

The following machines will also be required:

- Rotary Grass Slasher for maintenance of road sides and drainage channels.
- Grain, bag and bale elevator for stacking bags, loading grain, etc.
- Baler for baling rice straw for sale to cattle owners.
- Straw and cotton stalk chopper for pulverising straw or cotton stalk in the field if burning is unsuccessful, in order to facilitate cultivations.
- Elevated grain hopper with bagging-off spouts.
- Front-end loaders for four of the wheel tractors. These should be supplied with a materials bucket and fork lift attachments.
- Grain augers for transferring heaped grain into the grain hopper or into trailers.
- Mounted spinner-type fertiliser spreader.

3.2 Selection of Machine Type and Size - Irrigated Cotton

3.2.1 Tractors

The tractors used for the rice will also be used for the cotton. The crawler tractors will be used for the tillage and the wheeled tractors for fertiliser spreading, spraying, planting and inter-row work such as weeding.

3.2.2 Primary and Secondary Tilling

This will be carried out using the disc harrows as for rice. The stalks will be pulverised first using the straw chapper, as many as possible burnt and the remainder incorporated in the soil.

3.23 Planting

A four row unit planter with fertiliser attachments will be used for planting the cotton. In case maize is to be planted at a later date the planter will also be capable of planting maize. The row spacing will also need to be adjustable from 75 cm for cotton to 90 cm for maize. Seed will be acid delinted on site.

3.24 Fertilising

Fertiliser will be applied to the cotton area by spinner-broadcaster before planting and during the planting operation.

3.25 Inter-row Cultivation

There will be two types of inter-row cultivators; a tined type fitted with a combination of ducks feet and straight points and a rolling cultivator. The tined cultivator will handle heavy established weed infestations and the rolling cultivator will be a quick operation to handle small weeds and to break any soil cap that forms after irrigation.

3.2.6 Spraying

A normal tractor mounted sprayer will handle all spraying until plant height precludes the use of tractors. Final application of insecticides at the boll formation stage will be done manually using ultra low volume sprayers.

3.2.7 Picking and Bagging

Cotton picking and loose bagging will be carried out manually.

3.3 Machine Quantification

331 General

As discussed in Chapter 1, a maximum rice cropping intensity of 150% of the total surface irrigated area has been taken as the basis for the project. However, within this 150% total intensity there may well be variations from year to year in the hectarages grown in the qu and der seasons.

Several options were examined to calculate machine requirements. An extreme case was taken of 50% intensity in the gu and 100% intensity in the der and the effect on machine numbers compared with a 75%: 75% division. The only effect this extreme would have would be to increase the number of combine harvesters by two. The same effect also occurs if 100% intensity in the gu season and 50% in the der season are considered.

Since these extremes would require only minor adjustments to the machine numbers the 75%: 75% intensity is the most appropriate intensity on which machine requirements should be based.

3.3.2 Number of Days Available for Each Operation

A six day working week has been assumed for the purpose of calculating machine numbers, except in the peak periods covering March to May and July to September, when a seven day week has been taken.

(a) Der Season Rice Crop

The target area to be sown to rice for the der season crop is 1 539 ha (75% of the gross area). Of this, 513 ha will have been fallow during the preceding gu season, leaving 1 026 ha of the gu season rice crop to be cultivated. A summary of days available for each operation is shown in Table 3.1.

TABLE 3.1

Days Available for Mechanised Operations - Der Season

Operation	Area (ha)	Dates	Days available
Tillage	513	May 1st to Jul 20th	81 days gross 69 days net
(including levelling)	1 026	Jul 20th to Sep 30th	72 days gross 62 days net
Fertiliser spreading	1 539	Jul 8th to Aug 20th	44 days net 38 days gross
Drilling .	1 539	Aug 1st to Sep 30th	61 days gross 61 days net
Post-emergent spraying	1 539	Aug 20th to Oct 20th	61 days gross 52 days net
Transport - seed fertiliser, spray materials		Jul 21st to Oct 31st	102 days gross
			The June 2
Combine harvesting	1 539	Dec 8th to Feb 7th	62 days gross 50 days net
			V4311 2511
Transport grain		Dec 8th to Feb 7th	62 days gross 50 days net
		A STATE OF THE STA	Adams .

During the two tillage periods which have to be completed in 69 days and 62 days respectively, four operations have to be carried out by the crawler tractors. These consist of primary tillage, two passes of secondary tillage, and levelling. In order to estimate the minimum number of tractors required, the total net time available has to be split into individual periods for each operation. The allocation of the total time available between each operation is determined by the ratio of the work outputs for each operation. The output of each piece of equipment based on a 50 minute working hour is illustrated in Table 3.2.

TABLE 3.2

Output of Machinery (based on 50 minute working hour)

Machine	Field effic- iency (%)	Working width (m)	Working speed (kph)	Theor- etical output (ha/h)	Actual output (ha/h) (1)
90 hp Crawler					
Ploughing offset disc harrowing Offset disc harrowing Landplaning Levelling	85.00 85.00 85.00 85.00	2.30 3.65 3.00 4.00	5.00 6.50 8.00 8.00	1.15 2.37 2.40 3.20	0.81 1.68 1.70 2.27
75 hp Tractor					
Combination seed drill Spraying Stalk cutting Fertilising Spike tooth harrowing Planting Inter-row cultivation Post-emergence spraying	60.00 60.00 85.00 60.00 85.00 75.00 60.00	36.0 6.00 1.80 6.00 4.00 3.00 6.00	6.00 8.00 5.00 8.00 6.00 5.00 8.00	2.16 4.80 0.90 4.80 2.40 1.50 4.80 4.80	1.08 2.40 0.64 2.40 1.70 0.94 3.00 2.40
Combine harvester	60,00	4.00	3.00	1.20	0,60

Note: (1) Actual output is the theoretical output taken on a 50 minute hour basis, with a further reduction based on the field efficiency.

The days available for each operation for the two areas are summarised in Table 3.3.

TABLE 3.3

Days Available for Individual Land Preparation Operations - Der Season

	Primary tillage	Secondary tillage	Secondary tillage 2nd	Land- planing	Totals
Output (ha/h)	0.81	1.68	1.68	1.70	2.87
Time per ha (h)	1.23	0.60	0.60	0.60	
Days per operation: 1. 513 ha 2. 1 026 ha	30	14	14	11	69
	27	13	13	10	63

(b) Gu Season Rice Crop

The target area to be sown to rice for the gu season crop is also 1 539 ha. Again, 513 ha will have been fallow during the der season, leaving 1 026 ha of the der season area to be cultivated. The days available for each operation in the gu season are shown in Table 3.4.

TABLE 3.4

Days Available for Mechanised Operations - Gu Season

The same and the same.

2111111111111111			The State of the S
Operation	Area (ha)	Dates page 1	Days available
Tillage (including	513	Oct 1st to Jan 7th	98 days gross 80 days net
levelling)	1 026	Dec 8th to Apr 30th	144 days gross 121 days net
Landplaning	684 (1/3 gro	Jan 1st to Feb 28th	59 days gross 51 days net
Fertiliser spreading	1 539	Mar 8th to Apr 20th	44 days gross 38 days net
Drilling	1 539	Mar 16th to Apr 30th	46 days gross 46 days net
Post-emergent spraying	1 539	Apr 8th to May 20th	43 days gross 43 days net
Transport - seed fertiliser, spray materials		Mar 8th to May 20th	74 days gross
Combine harvesting	1 539	Aug 16th to Sep 30th	46 days gross 46 days net
Transport grain		Jul 21st to Sep 7th	49 days gross 49 days net

Since the tillage of the 1 026 ha will effectively follow the tillage of the 513 ha of fallow they can be taken together and treated as an area of 1 539 ha. Using the same methodology as for the der season tillage operations, the days available for each tillage operation are summarised in Table 3.5.

TABLE 3.5

Days Available for Individual Land Preparation Operations - Gu Season

	Prim a ry tilla ge	Secondary tillage	Secondary tillage (2nd)	Level- ling	Land- planing	Totals
Output (ha/h)	0,81	1.68	1.68	2.27	1.70	
Time per ha (h) Days per operation	1.23	0, 60	0.60	0.44	0.59	3.46
for 1 539 ha	72	35	35	25	34	201

(c) Cotton

TABLE 3.6

Days Available for Mechanised Operations of the Cotton Crop

Operation	Area (ha)	Dates	Days available
Stalk cutting	163	Feb lst to Mar 31st	60 days gross 51 days net
Primary tillage	163	Feb lst to Mar 31st	59 days gross 51 days net
Secondary tillage	163	Jun 1st to Jul 31st	61 days gross 51 days net
Pre-emergence spraying	163	Aug 1st to Aug 31st	31 days gross 31 days net
Planting	163	Aug 1st to Aug 31st	31 days gross 31 days net
Fertilising	163	Aug 1st to Aug 31st	31 days gross 31 days net
Harrowing	163	Aug 1st to Aug 31st	31 days gross 31 days net
Inter-row cultivation	163	Aug 21st to Oct 15th	56 days gross 48 days net
ULV spraying	163		2 days gross

3.3.3 Numbers of Machines Required

The output of each machine is calculated in Table 3.2. The number of machines required for the rice and cotton operations is shown in Tables 3.7 and 3.8 respectively. A 10 hour working day has been used on the basis that the machine operator will have an assistant operator to take over as and when required. A 20% service factor to make allowances for downtime for service repair is also included. The final columns in the tables establish the actual machine hours worked in order to calculate the operating costs of the machines.

Because many operations overlap, the number of tractors required is higher than that shown by the calculation of individual operations. The extent of this overlap is demonstrated in Figure 3.1 which shows the timing of the individual operations. From this it can be seen that the peak requirement for crawler tractors is during August and September when 6 machines will be required. The figure also indicates that the peak requirement for wheeled tractors occurs in the last half of August, when 17 tractors will be required.

The output of ULV sprayers is about 1 ha per hour. If 163 ha of cotton has to be covered in 2 days, then on the basis of an 8 hour working day, 11 sprayers will be required. Hand held battery powered ULV sprayers are sold in export packs of 45 and are very cheap (\$o\$h 575 each) when purchased in bulk. It is therefore recommended that one export pack of 45 be purchased.

It is impossible to estimate accurately the requirement for knapsack sprayers because the exact area for spot spraying each season is not known. It is proposed that 20 sprayers be purchased initially.

The total number of machines required, divided into 1985 and 1986 purchasing schedules, is given in Table 3.9.

3.3.4 Machine Utilisation

The actual machine time for the tractors, implements and combine harvesters are shown in Tables 3.7 and 3.8. The total number of machine hours are summarised in Table 3.10.

3.4 Training

The success of the project will rest very heavily on the ability of the workshops and the field staff to have machines ready at the right time and in the right quantities. Because of financial inducements offered to skilled personnel by the oil producing states in the Gulf there is a critical shortage of mechanical skills in Somalia. The training and retention of a skilled workforce on the project will therefore be of paramount importance.

Examination of Figure 2.1 illustrates the complex nature of the management of the mechanised operations. At one point in the der season there are ten operations occurring at once. Some of these operations require a high level of skill and supervision, e.g. combine harvesting, rice drilling, spraying and fertilising. It is therefore essential that key personnel be trained as quickly as possible. It cannot be expected that the Field Manager will be able to effectively carry out all of this training by himself. Similar problems of training will also arise in the maintenance and repair of the farm machinery.

It is therefore proposed that the project take advantage of the training facilities available from and often provided at a very reasonable cost by the manufacturers of the farm machinery. Initially, the manufacturers will supply instructors for the durations noted in the particular specifications. The cost of this training will be written into the contract.

Number of Machines Required

Rice - 75% Gu Season and 75% Der Season

Operation	Are (he)	Days avail-	Hours worked	Pla	Working . ha/	ha/ machine	Theor- etical	Service factor percentage	Actual number of	Machine	Machin
Gu sesson (75% of area cropped)					ì		machines	downtime	machines	(actual wor	king tim
Ploughing	1 539.00	72.00	10.00	0.81	8.10	583.20	2.64	20		190	1 900
Disc herrowing (first pass)	1 539.00	35.00	10.00	1.68	16.80	588.00	2.62	02	9	92	916
Disc harrowing (second pass)	1 539.00	35.00	10.00	1.68	16.80	588.00	2.62	20	4	92	916
Land planning	684.00	34.00	10.00	1.70	17.00	578.00	1.18	20	7	9	402
Levelling	1 539.00	25.00	10.00	2.27	22.70	567.50	2.71	22	4	89	678
Fertiliser spreading	1 539.00	38.00	30.00	2.40	24.00	912.00	1.69	20	2	3	641
Seed drilling	1 539.00	46.00	10.00	1.08	10.80	496.80	3.10	20	4	143	1 425
Spraying	1 539.00	43.00	10.00	2.40	24.00	1 032.00	1.49	20	2	3	3
Combine harvesting	1 539.00	46.00	10.00	09.0	00'9	276.00	5.58	20	7	152	2 565
Der sesson (75% of area cropped)											
Ploughing	1 026.00	27.00	10.00	0.81	8.10	218.70	4.69	20	9	127	1 267
Disc herrowing (first pass)	1 026.00	13.00	10,00	1.68	16.80	218.40	4.70	20	9	19	119
Disc harrowing (second pass)	1 026.00	13.00	10.00	1.68	16.80	218.40	4.70	20	9	19	119
Levelling	1 026.00	10.00	10.00	2.27	22.70	227.00	4.52	20	9	45	452
Ploughing (fallow)	513.00	30.00	10.00	0.81	8.10	243.00	2.11	20		63	633
Disc harrowing (fellow) (first pess)	513.00	14.00	10.00	1.68	16.80	235.20	2.18	20	n	ሂ	305
Cisc harrowing (fellow) (second pess)	513.00	14.00	10.00	1.68	16.80	235.20	2.18	20	n	ĸ	305
Levelling (fallow)	513.00	11.00	10.00	2.27	22.70	249.70	2.05	20	n	2	226
Fertiliser spreading	1 539.00	38.00	10.00	2,40	24.00	912.00	1.69	20	n	99	641
Seed drilling	1 539.00	61.00	10.00	1.08	10.80	658.80	2.34	20	^	143	1 425
Spraying	1 539.00	52.00	10.00	2.40	24.00	1 248.00	1.23	20	~	99	189
Cambles Languages	00 000	00.00	000	0	8	400 00	× 13	20	r	200	2 ECE

TABLE 3.8

Number of Machines Required Cotton

Operation	Area (ha)	Days avail- able	Hours worked per day	he/h	Working rate ha/dey	he/ machine	Theo- retical number of machines	Service factor percentage downtime	Actual number of machines	Machine Machine days hours (actual working time)	Machine hours rking time)
Stalk slashing	163.00	51.00	10.00	0.64	6.40	326.40	0.50	20	1	25	255
Ploughing	163.00	51.00	10.00	0.81	8.10	413.10	0.39	20		20	201
Disc herrowing (first pass)	163.00	26.00	10,00	1.68	16.80	436.80	0.37	20	7	10	76
Disc herrowing (second pass)	163.00	26.00	10.00	1.68	16.80	436.80	0.37	8	-	10	6
Pre-emergent spraying	163.00	31.00	10.00	2.40	24.00	744.00	0.22	8	-	1	8
Fertilising	163.00	31.00	10.00	2.40	24.00	744.00	0.22	82	7	2	89
Spike tooth harrowing	163.00	31.00	10.00	1.70	17.00	527.00	0.31	20	1	10	96
Planting	163.00	31.00	10.00	0.94	9.40	291.40	0.56	20	-	17	173
Inter-row cultivating	163.00	24.00	10.00	3.00	30.00	720.00	0.23	20	1	8	Z.
Inter-row cultivating	163.00	24.00	10.00	3.00	30.00	720.00	0.23	20	1	8	24

TABLE 3.9

Machinery Requirement : 1985 and 1986

Machine	1985	1986	Total Nr
90 hp crawler tractor	4	2	6
75 hp 2WD tractor	7	3	10
75 hp 4WD tractor	4	3 2	7
Combine hervester	5	2	7
Ploughing offset disc harrow	5	1	4 (1)
Offset disc harrow	4	2	6
Land plane .	2	0	2
Seed drills	3	1	4
Sprayers - tractor	3 2	1	3. (2)
Sprayers - LGP	1	1	2 (2)
Spike tooth harrow	i	1,741,00000	1
Cotton planter	1	0	ī
Fertiliser spreader	3	0 0 1	4
Inter-row cultivator	1	0	1
Rolling cultivator	1	0	1
Grass slasher	1	0	1
Cotton stalker & straw slasher	1	0	1
Rectangular baler .	1	0	1
Front end loaders	4	0	4
Grain augers	2	0	2
Grain, bag & bale elevator	2	1	3
Tine cultivator	2	0	2 3 2 8 7
4 wheel 5 t trailer	6		8
7 t grain trailer	5	2	7
Knapsack sprayer	14	2 2 6	20
ULV sprayer	45	0	45 (3)
Elevated grain hopper	1	0	1

Notes:

- (1) In Table 3.7 the maximum number of ploughing disc harrows calculated is 6. These calculations are based on sequential operations, i.e. all the tractors carrying out primary tillage, at the same time and then all going on to do secondary tillage. This assumption has been made to ease calculation of tractor numbers. In actual practice different tillage operations will be occurring at the same time as secondary tillage. Four ploughing offset disc harrows are therefore considered sufficient to carry out all primary tillage operations.
- (2) Final quantities of each type to be decided in 2nd year.
- (3) One export pack of 45.

TABLE 3.10

Total Number of Machine Hours

90 hp crawler tractor 4 812 4 410 395 9 617 10 10 579 6 1 763 75 hp wheeled tractor 2 707 2 701 4 7001 4 7001 4 7001 4 7001 4 7000 2 701 4 7001 4 7000 2 701 4 7001 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 701 4 7000 2 7000 2 7000 2 7000 2 7000	Machine	Gu season	Der season	Cotton	Total	Percent non- productive	To tal hours	Number of machines	Hours per machine
Or 2 707 768 6 182 30 8 036 17 Ow 1 900 201 4 001 - 4 001 4 1 832 1 832 194 3 858 - 4 001 4 402 - - 402 - 3 858 6 6 678 678 - - 1 356 - 1 356 4 641 641 68 1 350 - 1 350 4 641 641 68 1 350 - 1 350 4 641 641 68 1 350 - 1 350 4 - - - 96 96 - 96 1 - - - - - 96 96 - 96 1 - - - - - - 96 1 - - - - - -	Bwler tractor	4 812	4 410	395	9 617	10	10 579	9	1 763
0w 1900 1900 201 4 001 - 4 001 4 402 - - 402 - 3 858 6 402 - - 402 2 678 - 1 356 - 402 2 678 - 1 356 - 402 2 641 641 68 1 350 - 1 350 3 641 641 68 1 350 - 1 350 4 641 641 68 1 350 - 1 350 4 641 641 68 1 350 - 1 350 4 641 68 1 350 - 1 350 4 641 68 1 350 - 1 350 4 641 641 68 1 350 - 1 350 4 642 641 68 1 350 - 1 350 4 642 641 68 1 350 - 96 96 - 641 641 68 1 350 - 173 1 7 - - - - 108 1	neeled tractor	2 707	2 707	768	6 182	30	8 036	17	473
1832 1832 194 3858 - 3858 6 402 - - 402 - 2 678 - 1356 - 402 2 1425 - 1356 - 4 641 641 68 1350 - 1350 4 641 641 68 1350 - 1350 4 - - 96 96 - 96 1 - - 1773 1773 1 - - 108 108 - 108 1 - - 255 255 - 5130 7	nd disc harrow	1 900	1 900	201	4 001	1	4 001	4	1 000
402 - 402 - 402 2 678 - 1356 - 4 4 1425 - 1425 - 1425 4 641 641 68 1350 - 1350 4 641 641 68 1350 - 96 1 - - 96 96 - 96 1 - - 173 173 - 96 1 - - 108 108 - 108 1 - - 255 255 - 5130 7	lisc harrow	1 832	1 832	194	3 858		3 858	9	643
678 678 - 1356 4 1425 - 1425 - 1425 4 641 641 68 1350 - 1350 3 641 641 68 1350 - 1350 4 - - 96 96 - 96 1 - - 173 173 - 173 1 - - 108 108 - 108 1 - - 255 255 - 5130 7	ane ane	402	Ĭ	ı	402	ì	402	2	201
1425 1425 - 1425 4 641 641 68 1350 - 1350 3 641 641 68 1350 - 1350 4 - - 96 96 - 96 1 - - 173 173 - 173 1 - - 108 - 108 1 - - 255 255 - 255 1 - - 255 - 5130 7	eller	678	678	1	1 356	ï	1 356	4	339
641 641 68 1350 - 1350 3 641 641 68 1350 - 1350 4 96 96 - 96 1 173 173 - 173 1 255 255 - 5130 7		1 425	1 425	1	1 425	i	1 425	47	356
641 641 68 1350 - 1350 4 96 96 - 96 1 173 173 - 173 1 108 108 - 108 1 - 255 255 - 5130 7		641	. 641	89	1 350	ñ	1 350	3	450
96 96 - 96 1 173 173 - 173 1 - 108 108 - 108 1 - 255 255 - 5130 7	er snreader	641	641	89	1 350	3	1 350	4	338
cultivator 173 173 - 173 1 her 108 108 - 108 1 harvester 2 565 2 565 - 5 130 7	oth harrow	1	ı	96	96	1	96	1	96
cultivator 108 108 - 108 1 her - 255 255 - 255 1 harvester 2 565 2 565 - 5 130 7		1	Ē	173	173	ı	173	1	173
2 565 2 565 - 255 - 255 1 2 565 2 565 - 5 130 - 5 130 7	weiltivator	1	•	108	108	3	108	1	108
vester 2 565 2 565 - 5 130 - 5 130 7	sher	1	ı	255	255	ì	255	1	255
	harvester	2 565	2 565	Ę	5 130	1	5 130	7	733

The above figures do not include tractor and trailer transport operations. These are calculated as follows:

Approx. 46 days at 10 hours per day for 6 tractors and trailers = 2 760 hours. Approx. 50 days at 10 hours per day for tractors and trailers = 1 800 hours.	Approx. 30 days for 1 tractor = 300 hours. Approx. 42 days for 2 tractors = 840 hours.	Approx. 21 days for 3 tractors = 630 hours. Approx. 20 days for 1 tractor = 200 hours. Approx. 42 days for 2 tractors = 840 hours. Approx. 35 days for 3 tractors = 1 050 hours.	Approx. 10 days for 1 tractor = 100 hours.
1.1	1	1	1
Gu season Der season	Gu season	Der season	
Grain transport	Drilling		Cotton

Total tractor and trailer hours = 8 520 hours.

Total 75 hp tractor hours including transport is then 6 182 + 8 520 = 14 702 plus 30% for non-productive running around = 19 113 hours. With a total of 17 tractors each tractor does 1 124 hours per annum. With a total of 15 trailers each trailer does on average 1 274 hours.

CHAPTER 4

OPERATION AND MAINTENANCE

4.1 Mechanical Plant for Operations and Maintenance

The required procurement programme not only makes provision for vehicles and equipment for agricultural purposes, but is also required for the operation and maintenance of the civil and building works of the project.

There will be an overlap in the vehicles and equipment required for agricultural purposes and for operation and maintenance, particularly in the provision of workshop equipment and tools. The proposals have taken this into consideration.

The workshops have been designed to accommodate the repair of the vehicles, plant and equipment which will be necessary for agriculture at full development and for operation and maintenance for civil and building works.

The equipment required for the Mogambo Irrigation Project for operation and maintenance is, essentially, as follows:

- Bicycles, motorcycles, personnel and load carrying vehicles.
- Agricultural tractors, associated equipment and trailers.
- Excavators, grader and wheeled loader.
- Low load trailer.
- Water pump and concrete mixer.
- Workshop and maintenance equipment.

The levels for the provision of spare parts have been defined and the costs of these spare parts have been included in the Engineer's estimates.

4.1.1 Selection

A proportion of the fleet of vehicles and plant proposed for agriculture can be used for operation and maintenance but, in addition, the vehicles and plant required for operation and maintenance are listed in Table 4.1. Dredgers are not included as these are scheduled to be provided in Year 15. (See Additional Study for an Alternative Development, March 1980.)

No provision has been made for a mobile workshop or a compressor with tools. The mobile workshop is not considered necessary as work can be carried out on site using hand tools and portable equipment, which will be carried on the flat bed truck provided with a 12 t hydraulic arm crane, together with a welding set. The need for a compressor and tools could be infrequent, perhaps once a year when compressed air is really necessary and then a compressor and tools could be obtained for short periods from elsewhere, possibly from the Juba Sugar Project.

Some amendments to the Alternative Study for an Alternative Development requirements have been made as follows:

(a) Previously proposed were three agricultural tractors plus three general purpose trailers, one water tank trailer and one flail.

TABLE 4.1

Vehicles and Plant for Operation and Maintenance

Item	Utilisation	Number
Bicycles	General use General maintenance	30 1
Flat truck with cargo crane	General transport	1
Tipper truck	General maintenance and for the disposal of silt	2
Concrete mixer	General repairs	1
Water tank trailer	Domestic supply	1
Fuel tank trailer	For pumps and plant	1
Flail unit	For cutting vegetation on canal banks down to water level	1
Dragline excavator	Desilting intake channel and settling basin	1
Hydraulic backhoe excavator	Desilting main drain	1
Hydraulic backhoe excavator	Cleaning distributaries	1
Grader	General use	1
Low load trailer	General use	1
Loader	General use and for loading lorries, particularly any accumulation of dried out silt which has been dredge out by excavators	1 d
Water pump	General use	1
Workshop and field maintenance equipment	General use and for the maintenance of housing	l lot

Note: The determination of the numbers of vehicles and plant and equipment items for agriculture takes into account the requirements for operation and maintenance. Those items of common use are not listed in this table but are as follows:

Motor cycles
Estate car/Station wagon
Pick-up
Flat trucks as cargo carriers
Agricultural tractors (wheeled and tracked)
Agricultural trailers
Front end loaders (for agricultural tractors)
5 000 litres parked fuel bowser (field operations)

An allowance has now been made in the selected numbers of agricultural tractors and trailers proposed for agriculture to cater for operation and maintenance with, as before, one water tank trailer of 2 000 to 2 500 litre capacity and one flail unit.

In addition it is now proposed that a fuel tank trailer of 2 000 to 2 500 litres be provided in addition to the 5 000 litre fuel tank trailer to be parked adjacent to field operations.

- (b) Front loader equipment to be fitted to wheeled tractors is now proposed for agricultural operations and for operation and maintenance.
- (c) The number of crawler tractors, with bulldozer equipment, selected for agriculture, takes into account the requirements for operation and maintenance. The need for a larger bulldozer cannot be justified and the standardisation of a common type of crawler tractor for both agriculture and for operation and maintenance has obvious advantages.
- (d) Two hydraulic backhoe excavators have been added and also a wheeled loader.
- (e) The numbers of motorcycles, estate cars/station wagons and pick-ups neded for personnel transport takes into consideration both agricultural operations and operation and maintenance. The provision of bicycles is linked primarily to operation and maintenance.

Explanatory comment on each item selected for operation and maintenance is contained in the following sections.

(i) Bicycles

These should be of a basic type with a wheel size of 26 in. for general use.

(ii) Motorcycles

Motorcycles to be provided for the use of block supervisors, ditch riders and irrigation supervisors can all be of the same type, usually known as trial machines for off-the-road use, and of 125 cc capacity.

(iii) Personnel vehicles

The requirements for operation and maintenance are one station wagon plus two pick-ups for the dual role of personnel/goods carrying.

All these vehicles should be four wheel drive, long wheelbase and fitted with diesel engines as diesel fuel will be more readily available for general use.

(iv) Flat bed truck

This vehicle can be made much more work effective by being fitted with a cargo crane mounted behind the cab. With a capacity of 10 to 12 t the hydraulic arm will have a lifting capability to load, to the bed of the lorry, both irrigation pumps and engines from ground level. This vehicle can also serve as a travelling crane, suitable for most of the lifting duties envisaged.

The vehicle loads are expected to be approximately as follows:

Gross vehicle weight	PD Palaina	160 000 kg
less weight of chassis cab	4 500 kg	
hydraulic crane arm	2 000 kg	led light t
flat body	1 500 kg	1 665
	8 000 kg	8 000 kg
pay	y load	8 000 kg

A length of flat body of about 5 m would be appropriate for the payload and would be suitable for the requirements of the project in operation and maintenance. A bolster over the cab would be useful for carrying extra long loads.

(v) Tipping Trucks

The tipping trucks could be of the same type as the flat deck truck above. Excluding the weight of the cargo crane and with a shorter body of about 4 m the payload would be in the order of 10 000 kg.

(vi) Low bed trailer

This trailer has been specified to have an adequate load carrying capacity to transport the crawler tractors. The only other machine of greater weight to be carried is the larger of the backhoe machines where the operating weight could be in the order of 17 tonnes.

If the low bed trailer can be restricted to a payload of 10 tonnes then the trailer can be towed on a good surface by an agricultural tractor or on a poor surface by a crawler tractor. To contemplate the purchase of a tractor and trailer combination to handle the larger backhoe would require expenditure at a level of about £45 000 which could not be justified. If the larger backhoe machine has be to transported to the workshops then the low loader unit at the Juba Sugar Project, or elesewhere, could possibly be utilised.

(vii) Agricultural tractors

Of the agricultural tractors to be purchased it is proposed that four should be rigged with front loaders and one other with a flail unit.

This combination of agricultural tractors, trailers and attached equipment should satisfy the needs of the project in operation and maintenance. The duties will vary according to the season as some of the equipment is only required at certain times of the year.

(viii) Agricultural trailers

These general purpose trailers are not tipping trailers. Although they are required to operate in support of labour intensive operations the trailer is intended to be sufficiently robust to be loaded by the loading shovel and also to carry the smaller items of plant.

(ix) Front loader

This front loading shovel equipment for the agricultural tractor is intended to have the capability of loading loose material on to the tipper truck.

(x) Flail

The tractor mounted flail has a two piece boom as the longer reach of the three piece boom is not necessary. When the flail is dismounted from the tractor the counterweight could remain fitted, thereby improving grip for other operations. However, the haphazard removal of the flail unit from this tractor to enable the tractor to be used for other operations, should be discouraged as there should be enough work to keep the flail reasonably well employed.

(xi) Water and fuel tank trailers

These are similar, with variations to suit the liquids which are being carried. Coupling is to the agricultural tractor, where the trailer parking wheel and jacklegs keep the connection at the correct level for re-coupling to the agricultural tractor.

For the supply of domestic water (when this is required) a tank capacity of up to 2 500 litres is considered to be adequate.

Fuel is normally delivered by the project's tanker truck but when ground conditions become difficult, in the wet season for instance, fuel could be delivered by this fuel tank trailer towed by an agricultural tractor or by crawler tractor where necessary, the fuel being discharged either by gravity or by the semi rotary pump provided.

(xii) Dragline

The duties at the dragline were examined in relation to the reach required for desilting the intake channel and settling basin. The intake channel with a bed width of 10 m and a channel depth of 6 m, with bank slopes of 1 to 2 (vertical to horizontal) indicates that a machine with a reach of 21 m would be adequate working from both banks. A dragline with the capability of the NCK 605 could meet these requirements with the standard bucket size of 2 cubic yards (1.5 cu.m).

If the jib was lowered to say 28 degrees then the reach could be extended to 31 m by throwing the bucket. This would be necessary to reach the centre of the widest section of the settling basin where, with a bed width of 36 m and a depth of 3.4 m, a reach of 28 m is

required to excavate at the centre. To make this a practical proposition a jib length of not less than 24.5 m would be required, rigged at a flat angle down to 28 degrees and a 1 cubic yard (0.75 cu.m) Hendrix type dredging bucket would be utilised. This would normally keep clear the whole of the settling basin.

To complete the study the reach of the hydraulic excavator with the maximum outreach of 15 m was considered for the requirement of desilting the intake channel. With a requirement of 21 m to reach the centre line of the channel, from both banks, the 15 m reach of the best hydraulic backhoe thought to be currently available was not adequate.

The dragline machine is therefore the only machine capable of desilting the intake channel and settling basin.

For the desilting operations in the intake channel and desilting basin the choice is as follows:

Flat jib at say 28 degrees For settling basin

Probably not less than 24.5 m jib 0.75 cu.m Hendrix type bucket.

Normal jib elevation of say 42 degrees 18.3 to 21.3 m jib length For the intake channel:

1.5 cu.m Hendrix type bucket.

It is also envisaged that the dragline will become engaged in some desilting operations for the flood relief channel where the bed width is in the order of 55 m which is well in excess of the reach of the dragline specified.

There are, at present, two NCK 605 dragline machines already working at the Juba Sugar Project on maintenance of inlet channels. The possibility of being able to utilise a NCK 605 long jib dragline excavator from the Juba Sugar Project at Mogambo should be considered in order to reduce the capital expenditure for operation of maintenance work.

Hydraulic backhoe excavators (xiii)

It is recommended that the use of the dragline machine be confined to the intake channel and settling basin in order to conserve the life of this machine.

To move this dragline to work down the main canal would be wasteful and unnecessary and it is therefore proposed that two further hydraulic backhoe excavators be purchased, one for the maintenance of the main canal and a smaller machine for the maintenance of the drains and distributary channels. This type of hydraulic backacter machine has proved to be ideal in these applications where the shape of the channel is important and where overcutting is to be avoided. This type of excavator can also carry out the weeding as well as silt removal.

The main canal, with a bed width of 8 m and a depth of 2 m, could be maintained with an excavator working from one bank only, if a reach of about 19 m is obtainable, but an excavator with such a reach may not yet be readily available. To reach only to the centre of the bed of the main canal calls for a reach in the order of 11 to 12 m, which is within the reach capability of the more common range of long reach hydraulic backhoe machines.

The distributary channels, with bed widths varying from 1.5 m to 4 m and channel depths varying from 0.8 m to 1.5 m, respectively, are within the range of many makes of hydraulic backhoe excavators. Using the advantage of working from one bank only precludes the use of backhoe machines in the mini-excavator sizes. The use of long reah backhoe machines for smaller distributaries is also not suitable as the machine would have to stand well back from the channel in order to be able to work effectively.

(xiv) Grader

The size of the grader which has been specified is in keeping with the operational conditions experienced in projects in Somalia.

(xv) Bulldozer

The size of the bulldozer for operation and maintenance can be the same as for agriculture and the specification is based upon this consideration.

The operational life of this bulldozer can be conserved by the use of the grader. To run the tracks off the bulldozer in minor work is wasteful and should be avoided.

(xvi) Wheeled loader

The wheeled loader will be in great demand within the project having many applications in operation and maintenance.

It is expected that silt removed from the irrigation channels will be dumped on the bank. In certain areas this silt will have to be loaded on to a lorry, by the loader, for dumping elsewhere. To meet this maintenance two tipper trucks will be required to ensure a reasonable balance with the output of the wheeled loader.

(xvii) Water pump

A diaphragm type water pump has been chosen in preference to a centrifugal pump, largely because of the relatively small water flows which can be expected and because the diaphragm type pump can handle a large proportion of solids and can run even when sucking air and water, for long periods, without detriment.

(xviii) Concrete mixer

This has been chosen at an adequate size to be robust, portable and with a tilting drum.

(xix) Workshop and field maintenance equipment

Equipment would normally be held at the base workshop but it is expected that it would also be utilised in field maintenance and repairs. This workshop and field maintenance equipment is considered under the following main headings:

- (a) Machine tools for the main workshop, comprising:
 - centre lathe;
 - benchgrinder with green silicon wheels for tungsten carbide tipped tools;
 - radial drilling machine;
 - twist drill regrinding machine;
 - valve refacing grinding machine;
 - heavy duty pedestal grinder;
 - lighter bench mounted grinding machine;
 - powered hacksaw:
 - garage type compressor;
 - battery charger;
 - medium size shaper.
- (b) General tools and equipment and measuring instruments.
- (c) Equipment for the inspection and reconditioning of fuel injectors for diesel engines.
- (d) Socket sets and spanners.
- (e) Files and drills.
- (f) Hand operated travelling lifting frame.
- (g) Lifting slings.
- (h) Sawbench for carpenter.
- (i) Lighting set.
- (j) Tractor mounted welding set.

Operation and Maintenance for Housing, Administration Buildings and Services

The requirements for operation and maintenance of housing, adminstration buildings and services were covered in the Supplementary Feasibility Study. The costs were assessed on a percentage basis of the capital cost and these have been updated together with the increased cost of fuel where appropriate.

It is now estimated that the housing contract will be complete in September 1984 and with a year's maintenance period very little input apart from running fuel costs will be needed before September 1985.

Costs allied to labour and staff are allocated in another section of this report. The following summaries show the make-up of the other costs involved.

4.2.1 Materials and Spares Costs

Total capital cost of buildings = SoSh 50 857 455

Therefore annual costs of materials and

spares at 1.5% = SoSh 762 862

Total capital cost of roads = SoSh 1 289 300

Therefore annual costs of materials

at 2% = SoSh 25 786

Total capital costs of sewerage,
potable water and electrical supply = SoSh 98 291 130

Therefore annual cost of materials and spare parts at 1% = SoSh 98 291

Therefore total annual cost of spare parts and materials at 1984 prices = SoSh 886 939

Allowing 5% Inflation.

Total cost for 1985 = SoSh 931 286

Maintenance by the contractor is complete by September 1985

therefore allowance for 1985 = SoSh 232 820

Total cost for 1986 = SoSh 977 850.

4.2.2 Operating Costs

The main cost involved is the fuel costs for the generators. For the generators on site it is assumed that 600 litres per day of diesel will be required. For 1984 assume 5 months in the year will be required.

Cost of diesel for 1984 assumed at SoSh 5/litre

Therefore cost for 1984 = SoSh $5 \times 600 \times 30 \times 5$

Lubrication costs are assumed at 10%

of fuel cost = SoSh 450 000

Therefore lubrication costs = SoSh 45 000

Assuming 10% inflation per annum for diesel

Cost for 1985 = SoSh $600 \times 365 \times 5.5$

Lubrication costs = SoSh 1 204 500

Cost for 1986 = SoSh 1 204 500 x 1.1

= SoSh 1 324 950

Lubrication costs = SoSh 132 495.

4.3 Operation and Maintenance for the Irrigation and Drainage System

Once again these costs are based on the Supplementary Feasibility Study.

It is estimated that the Irrigation and Drainage Contract will be completed in March 1986 and thereafter the Contractor has to complete one year's maintenance.

The costs of staff, labour and maintenance of equipment for operation and maintenance are covered elsewhere.

4.3.1 Materials and Spares Costs

As the Contractor's maintenance period is not complete until March 1987 no materials or spares will be required during 1985 and 1986. The costs of running the mechanical equipment for maintenance of channels, etc. is allowed in another section.

4.3.2 Operating Costs

The fuel and oil costs are based on quantities shown in the Additional Study for an Alternative Development with the costs of diesel updated to the current duty free cost of SoSh 5/litre.

From the Additional Study the following costs are noted at full development of 1 539 ha of surface irrigated rice and 163 ha of sprinkler irrigated cotton:

C	1		C-CL
COSES	annum	m	2020

Main irrigation pump station	530 000
Sprinkler pump station	162 000
Drainage pump station	19 000

Recalculating these to 1984 costs, allowing SoSh 5/litre for diesel, adjusts these figures to:

	505h/annum
Main irrigation pump station	2 284 480
Sprinkler pump station	698 275
Drainage pump station	81 900-

To suit the proposed programme of:

	198	5	1986	
Rice crop (ha)	Gu 459	Der 900	Gu 1 539	Der 1 539
Cotton crop (ha)		122		163

and allowing for 10% inflation per annum for fuel costs, the total fuel costs are as follows:

	1985 SoSh	1986 SoSh
Main irrigation pump station Sprinkler pump station Drainage pump station	1 109 508 574 898 39 169	2 764 220 844 913 99 099
Totals	1 723 602	3 708 232

CHAPTER 5

MANAGEMENT AND STAFFING

5.1 Present Status

The primary aim of this chapter is to establish the staff needed to implement both the agricultural programme successfully and thereafter to operate and maintain the project. From this a recruitment schedule upon which a staff recurrent cost budget can be based is also established. This chapter therefore reviews the present status of the project in terms of organisation and staffing and thereafter produces an estimate of staff required to operate the project for the first two years.

5.1.1 Existing Staff

A project headquarters has been established in Mogadishu, and over the years since the project was initiated, a cadre of Somali managerial and support staff have been recruited. As of February 1984, headquarters staff numbered around 46 persons, made up of the following:

- General Manager
- Irrigation Engineer
- Head of Administration
- Chief Accountant
- Two Agronomists/Agricultural Managers
- Two Senior Accountants
- Personnel Manager
- Procurement Officer
- Junior staff comprising clerks, typists and drivers, etc. making up the balance of the 46.

Of the senior staff, an agronomist is stationed on site. His principal task is to manage the small banana farm which was purchased by the project, and to act as site agent for the client. The agronomist is supported by a radio operator, driver, foreman and a labour force varying between 10 and 30, which is needed to maintain the banana farm.

5.1.2 Management Organisation

A management study aimed at defining an appropriate management organisation for the project was carried out during the early part of 1983. This report did not clarify in any further detail the management which was shown in the 1980 Alternative Development Report.

The Alternative Development Report proposed an organisation comprising three major departments; Operations, Accounts and Administration, to be presided over by a Board, General Manager and Deputy Manager. Of these departments, Operations was particularly diverse incorporating Farm Management, Agronomy and Irrigation Engineering sections. On a scheme of this size there is little scope for an alternative organisational structure and the only issue which is worth considering at this stage, is whether Engineering and Agriculture, the major elements central to the successful operation of the scheme, should be established as separate departments.

The Engineering component is particularly diverse, involving:

- operation and maintenance of irrigation and drainage works;

operation and maintenance of civil and building works;

- operation and maintenance of a wide range of heavy plant (stationary and mobile).

Agriculture is also diverse, incorporating field management, agronomy and agricultural engineering and would probably be more easily managed if established as a separate department.

The comprehensive mechanical workshop would be complementary to both the Engineering and Agricultural departments.

Although the organisation of existing staff into discrete departments is not yet formalised, they could clearly be organised into four main departments: Accounts, Administration, Agriculture and Engineering. In terms of existing staff numbers, the Accounts and Administration departments are already well established.

5.2 Proposed Organisation and Staffing

5.2.1 Headquarters

The proposed organisational structure for the project headquarters staff at Mogambo, including the factory organisation is shown in Figure 5.1. The agricultural operation comprises four main departments: Accounts, Administration, Engineering and Agriculture. The proposed complement of staff, excluding the factory requirements, at Mogambo headquarters is given in Table 5.1. This table indicates the timing of recruitment of headquarters staff and the incorporation of existing professional staff into the management structure.

5.2.2 Field Management and Agricultural Labour

(a) Field Management

CONTROL

It is proposed that the scheme is divided into smaller management units to be known as sections. To avoid excessive distances between the labourers' villages and their place of work each section would have its own permanent labour force. Whilst it is desirable that labour will ultimately identify with a particular section, it may be necessary in the early years for labour from one section to help out from time to time in another.

Four sections are proposed. They have been determined primarily on the basis of:

- size, with the aim of standardising size as far as possible;
- methods of irrigation; surface or sprinkler;
- independence of irrigation operation.

The four sections (three surface irrigation and one sprinkler) are defined in Table 5.2. The surface irrigation sections are 702, 675 and 675 ha in area, and as each is in the command of a specific night storage reservoir (Section 1 is served by two reservoirs), they have maximum independence in terms of irrigation operation.

Proposed Organisational Structure




TABLE 5.1

Mogambo Irrigation Project - Project Staff Requirements: Project Headquarters

			e	R	ecruitment of Jan to Jun	f staff	1986
Position	Expatriate or local staff	Total Nr	Existing staff Feb 1984	1984 Nr	1985 Nr	1985 Nr	Nr
Management					,	ī	1
General Manager	S	1	1	1	1	î	î
Secretary	S	1	1	1	i	î	î
Rice Farm Manager/Deputy General Manager	E	1		1	î	î	1
Secretary	S	1		1.	î	î	1
Drivers	S	2		i î	2	2	2
Watchmen	5	2		î	2	2	2
Labourers	S	1		î	ī	1	1
Gardeners Messengers	s	2		ī	2	2	2
Accounts Department						, ,	1
Chief Accountant	E	1		1	1	1	ī
Chief Accountant (Designate)	S	1	1	1	1 2	2	2
Senior Accountant	S	2	2	2	1	ī	î
Procurement Officer	S	1	1	1 2	3	3	1 3 2 1
Clerks	S	3		1	2	2	2
Typists	S	2	,	1	1	ī	1
Drivers	5	1	1	1	ī	ī	1
Chief Storeman	S	1		i	ĩ	ī	1
Storemen	5	1		î	î	ī	-1
Assistant Storeman	5	1		î	1	1	1
Stores Clerk	5	i		î	1	1	. 1
Typist	9	2		2	2	2	2
Labourers Fuel Distribution Clerks	S	2		2	2	2	2
Fuel Bowser Drivers	555555555555555	1		1	1	1	1
Administration Department						- 1	1
Senior Administrator	S	1	1	1	1	î	î
Personnel Officer	s s s	1	1	1	1	î	î
Training Officer	S	1	1	1	2	2	2
Clerks	5	2		î	2	.2	2
Typists Drivers	S	2		î	ī	1	1
Engineering Department							45
Irrigation Engineer	E	1	21	¥	1	1	1
Irrigation Engineer (Designate)	S	1	1	1	1	ì	1
Building Foreman	S	1		1	1	î	ī
Draughtsman	S	1		1	4	4	4
Labourers	S	4			i	í	1
Drivers	5	1			•	-	. 1
Agricultural Department	ε	2		2.	1	1	1
Field Manager	S	1	1	1	1	1	. 1
Deputy Field Manager Agricultural Machinery/Workshop Specialist	E	i	-	-	1	1	1
	S	ī	1	1	1	1	1
Agronomists Technicians	S	4	-		4	4	4
Typists	E S S	1		1	1	1	1
Labourers	S	4			4	4	4

TABLE 5.2

Definition of Management Units

Section number	Irrigation command	Number of units	Area (ha)	Comments
1	MIC1	17	459	M2C1 will be completed for gu 1986
	M2C1	9	243	3
		Total	702	*
2	M1C4	17	459	both commands completed for der 1985
	MIC6	8	216	
		Total	675	
3	M2C2	13	351	both commands completed for gu 1986
	M2C4	12	324	
		Total	675	
4	Sprinkler irrigated area	4	163	122 ha svallable der 1985, 163 ha for der 1986

Day-to-day operations in each section will be supervised by a Section Manager, who will be responsible to the Field Manager. Other supervisory support at the section level will include timekeepers, wages clerks and foremen. Foremen will be recruited at a ratio of one foreman to 20 labourers. Table 5.3 shows the number of field supervisory staff required between 1984 and full development in 1986.

(b) Machinery Operators

Machinery operators fall into three main groups :

- wheeled tractor operators;
- crawler tractor operators;
- combine harvester operators.

An operator and an assistant (trainee operator) will be assigned to each machine and a senior operator appointed for each group. The requirement for machinery operators is shown in Table 5.3. Overall management of machinery may have to remain the responsibility of the Field Manager although the case for appointment of a Mechanisation Manager is discussed in a later section of this report.

TABLE 5.3

Mogambo Irrigation Project - Project Staff Requirements: Field Management

1986 Nr	4 7 15	1 16 17	2 9	1 6
Recruitment of staff Jan to Jun Jul to Dec 1985 1985 Nr Nr	3 6 10	1 16 17	5 9	1 6 7
Recruitment Jan to Jun 1985 Nr	0 4 v	1 16 17	5 6	1 6 7
Aug to Dec 1984 Nr		1 11 12	4 3 1	
Existing staff Feb 1984	1.1.1	1 1 1	, , ,	1 t l
Total Nr	4 7 15	1 16 17	1 5 6	1 6
Position	Field Management Section Managers Time and Wages Clerks Foremen	Machinery Management Tractors: Senior Operators Operators Operators' Assistants	Crawlers: Senior Operators Operators Operators' Assistants	Combine harvesters: Senior Operators Operators Operators' Assistants

(c) Agricultural Labour Force

Table 5.4 shows the build up in labour force for each section. At full development in April 1986, the total unskilled labour force required for field operations would be around 290 persons. There would also be a requirement for casual labour for general field operations of just under 4 000 man days per year from 1986 onwards. This does not include cotton pickers who would add a further 200 casuals to the labour force of Section 4 for approximately 2 weeks in December, all of January and two weeks during the following February.

The need for bird scarers is unpredictable and the economics of comparing wages for bird scarers and potential losses due to bird damage will have to be assessed. Assuming a requirement of 1.5 persons per ha for a period of 30 days for each ha the requirement at full development would rise to 1 280 persons during August and September and January and February. During initial development, 380 persons would be required in August/September 1985 with 740 persons needed in January/February 1986. It is unlikely that bird scarers will be available in these numbers, particularly between December and February when bird scaring will coincide with cotton picking.

Protection from bird damage represents the most serious problem which project management will have to face and should be one of the immediate priorities of the Agricultural department.

5.2.3 Workshop

Under the proposed organisational structure the workshops will be complementary to both the Engineering and Agricultural departments. The workshop itself will be managed by the Workshop Foreman who will be supported by a complement of staff incorporating the range of skills, mechanical, electrical, carpentry, machining, etc., required to repair and maintain all project vehicles, plant and machinery. The staff required are shown in Table 5.5.

5.2.4 Irrigation Department

The staff for the operation and maintenance of the irrigation and drainage is based on figures for the Additional Study for Alternative Development, 1980, with the exception that the labour for the infield works now come under the supervision of field management.

Labour is retained, however, for the maintenance works involved in the main canals and drains which will be required in conjunction with the plant maintenance work. Table 5.6 shows the required build up and total numbers required.

5.2.5 Project Housing

Whereas the management staff will be based in the project headquarters village already constructed, the housing for other staff has still to be constructed. This will inevitably create problems, especially during the early stages of construction when staff are required to settle in and commence training. It should also be noted that the nearby Juba Sugar Project provides block built houses for their Somali staff for staff Grades 1 to 8. This will be an important factor to take into consideration in trying to bring staff to the Mogambo Irrigation Project.

	1985 3 F M A M 3 3	1985	<	s	0	z	Q	2	Σ L	۷ _	Σ	r	1986 J	<	s	0	z	۵	1987	787 F
10 13 19 80 82 79 69 70 20 20 40 70 70 70 70 70 70 10 10 11 1 1 2 4 4 4 4 4 600 man days		77 8	n		70 7	70 7	31 4 4 4 45 18	41 33 70 70 4 4 180 180	V 4 0 70 4 0	282		94 96 90 90 5 5 1 200 men	83 90 5 5 30 days	92 90 5 440	200 80	800	90 85	72 90 5 110	70 90 5 440	90 90 90 90 90 90 90 90 90 90 90 90 90 9
14 20 28 20 20 40 1 1 2 720 man days	14 20 28 20 20 40 1 1 2 nen deys	28 40	-	118 12 90 9	121 110 90 90 4 4		202	100 68 90 90 4 4 560 560	8 4 0 0 4 0 4 4 4 4 4 4 4 4 4 4 4 4 4 4	884		93 90 4 00 ms	91 93 84 90 90 90 4 4 4 1 200 men days	88 90 4 420	128 90 4 4	90 4	90 87	69 90 4	420	40
								10 15 20 20 1 1	22 22 1 2	8 8 ₹		90 93 90 90 90 90 90 90 90 90 90 90 90 90 90	84 90 4 an days 105	88 90 4 420	128 90 4	90 8	82 90 4	69 90 4	420	420
20 20 40 70 70 90 90 110 160 1 1 2 4 4 5 5 6 8 2 600 man days 95 380 380	90 90 110 5 5 6 nan days 95 380	011 6 380	- N		160 160 8 8	50 160 8 8 185		180 180 9 9 740 740	0 200 9 10	270	3,6	270 13	270 270 270 2 13 13 13 3 600 men deye 320 12	270 13	270 13 1 280	23	270 13	270 13	1 280	1 280
1 3 12 5 5 10 1 1 1 190 man days	1 3 12 5 5 10 1 1 1 1	10 10		20 2	2022	202	22 20 20 20 20 20 20 20 20 20 20 20 20 2	20 50 50 50 50 50 50 50 50 50 50 50 50 50	9 10 20 20 2 2 3 2 90(6)	7 50 7	6	20 20 20 20 20 20 20 20 20 20 20 20 20 2	- 2 3 0 20 20 2 2 2 260 men days	16 20 2	22.22	2 2 2	30 25 200(6)	30 25 200 200	16 25 200(6)	14

Notes

Based on Table 2.3.

Does not include Bird Scarers.

Assumes that surplus labour on Section 1 in October and November 1985 could be used on Section 2, Based on Table 2.4.

Does not include cotton picking.

Half month only. 888888

TABLE 5.5

Mogambo Irrigation Project - Project Staff Requirements: Workshop and Stores

Docition	Eventainto.	Total	Fulation	Aug to Dee	Jon to Jun	not of his and to her	1086
ionieo -	or local	Z	staff	1984	1985	1985	7.00
	staff		Feb 1984	Ż	Ż	Ż	Ż
Workshop Staff		i k				9	
Workshop Foreman	ш	Н		1	1	-1	-1
Foreman	S	7		7	7	7	7
Mechanics I	S	80		00	&	80	æ
Mechanics II	S	10			10	10	10
Vehicle Electrician	S	7			-	-	-
_abourers (semi-skilled)	S	14			10	14	14
Apprentices	S	6			~	6	6
Welder	S	н			-1	-	Н
Welder's Assistant	S	-			Н	-	-
Turner	S	1			-	-	Н
Turner's Assistant	S	4			-1	-1	-
Plumber	S	1			-	-	-
Plumber's Assistant	S	1			7	-	-
Electrician	S	7			-	-1	-
Electrician's Assistant	ဟ	H			Н	-	-
Carpenter	S	7			н	-1	Н
Carpenter's Assistant	S	Н			1	-1	7
Truck drivers	S	4			4	4	4
Drivers' Assistants	S	4			4	4	4
Watchmen	ဟ	4			4	4	4
Labourers	S	4			4	₫	4
Spare Parts Store							
Chief Storeman	Ŋ	4		-	-	-	-
Spare Parts Clerk	တ	Н		-	1	7	4
Typist	Ŋ	H		-	-	1	-1
Labourers	S	-		1	-	7	4

TABLE 5.6

Jan to Jun Jul to Dec 1986 1985 1985 Recruitment of staff ź 9 Mogambo Irrigation Project - Project Staff Requirements: Irrigation Department ž Aug to Dec 1984 ż Existing staff Feb 1984 Total Nr Expatriate or local staff Operation and Maintenance Staff Irrigation Supervisor (Designate) Position Irrigation Engineer Survey Assistants Operators

ź

14

10

9

8

20

14

10

20

14

Ditch Riders

Surveyor

Labourers

5.3 Management Organisation

The project management organisation is to be supported in the early years by an expatriate Agricultural Management Team comprising seven specialists, most of whom will be provided by a single firm currently engaged in agricultural management. Of this management team one member is a Rice Miller and as the organisation of the rice mill is outside the scope of this study, no comments are made on this position. Of the other six posts, one is an irrigation engineer who will be provided by the Mogambo Irrigation Project. The remaining specialists, who will be involved in the crop production operations have proposed inputs as follows:

		Duration of assignment (years)		
1. 2. 3.	Rice Farm Manager (Deputy General Manager)	3		
3.	Field Manager Chief Accountant	2		
4.	Agricultural Machinery/Workshop Specialist	2		
5.	Workshop foreman/mechanic	3		

It is planned that a minimum of 10% of the Farm will be farmed by small holders. The management team in liaison with the General Manager will formulate a policy to provide settlement and extension services for the small holders. Should it be proved necessary an agronomist may be added to the team, at a later stage, to assist in these settlement and extension services.

5.4 Implementation Schedule


Figure 5.2 illustrates the timing of the various activities which have to be carried out to enable the target cropping programme for 1985 and 1986 to be achieved. It assumes that land development and construction of irrigation and drainage works have been completed and they do not impede or restrict agricultural operations. The timing of field operations has been shown in detail in Figure 2.1, Figure 5.2 therefore is concerned primarily with:

- the recruitment and installation of management staff;
- the establishment of workshops and mechanical stores;
- the establishment of management, accounting, administration and stores procedures;
- the procurement of machinery vehicles and plant;
- staff training;
- procurement of agricultural inputs.

If the target area of 459 ha of basin irrigated rice in the 1985 gu season is to be achieved it is clear from Figure 5.2 that the first batch of agricultural machinery will have to arrive on site during November and December 1984 at the latest, if it is to be ready to commence operations in January 1985. Prior to this however, the workshop will have to be properly established, equipment installed, staff recruited and training underway. The Workshop foreman should therefore be in post early in September 1984.

A workshop equipped and operating effectively is essential if the initial servicing and assembly of agricultural machinery is to be achieved by the beginning of 1985.

Mogambo Irrigation Project Implementation Schedule



Notes: (1) De

- (1) Details given in Chapter 5
- (2) Including the agricultural labour force
- (3) Tractors, cultivating, planting and spraying equipment
- (4) Harvesting and grain handling equipment

CHAPTER 6

TRANSPORT

6.1 Types of Vehicles

The project will be orientated towards diesel powered machines. There is provision for bulk storage of diesel fuel and the workshops will be mainly concerned with the maintenance and repair of diesel engine powered machines. For vehicles, diesel engines also have the advantages of economy and price over equivalent petrol engined vehicles. It is therefore recommended that all vehicles to be purchased should be diesel engine powered. The motor cycles only will be petrol engined.

6.2 Number of Vehicles

The total requirement for transport vehicles is summarised in Table 6.1. Of these one Range Rover and three Land Rover pick-ups have already been provided by the funding agents. The balance, i.e. two estate cars, three 4 wheel drive station wagons, three 4 wheel drive pick-ups, one 3 tonne van, twelve motor cycles and four 10 tonne trucks will be purchased in 1985.

TABLE 6.1
Estimate of Requirement for Transport

Designated position	Type of vehicle	Number required	Estimated life (km)
General Manager Chief Accountant Administration Manager	Estate car	3	120 000
Deputy General Manager Agric.Mach/Workshop Specialist Irrigation Engineer Field Manager	4 wheel drive station wagon or estate car	4	150 000
Workshop Foreman Workshops (general including Maintenance and	4 wheel drive pick-up		
Stores)		6	150 000
Stores	3 tonne van	1	150 000
Deputy Field Manager (1) Section Manager (4) Maintenance and	Trail-type motor cycle		
Stores	12,7 00	12	50 000
General transport	10 tonne capacity truck (one fitted with cargo of		300 000

Note: No vehicles have been allowed for the Rice Mill requirements.

6.3 Running Costs

For the purposes of estimating running costs the following annual use for the vehicles has been taken :

机合分 医多形	(km)
Estate cars	25 000
4 wheel drive station wagons	25 000
4 wheel drive pick-ups	30 000
3 tonne van	30 000
Motor cycles	10 000
10 tonne trucks	50 000

CHAPTER 7

MECHANICAL WORKSHOPS AND STORES

7.1 General

The workshops will have to perform the following maintenance and repair functions:

- (1) Agricultural machinery
- (2) Project maintenance equipment (O & M)
- (3) Irrigation pumps and equipment
- (4) Estate maintenance
- (5) Vehicles

The stores will have to organise the ordering, handling, collection and storage of all project inputs for:

- (1) Agricultural machinery spare parts
- (2) Operations and maintenance equipment spare parts
- (3) Irrigation pump and equipment parts and materials
- (4) Vehicle spare parts
- (5) Tools
- (6) Fuel and oil

There are several factors which determine the type of facilities required in the workshop. These are :

- (a) A shortage in Somalia of any effective representation and distribution of major agricultural machinery manufacturers. Consequently, the project will have to be almost entirely selfsufficient in ordering and storing parts.
- (b) There are no known facilities for the overhaul of injectors and injector pumps in Somalia;
- (c) There are no high quality facilities for crankshaft regrinding, cylinder reboring or other machinery facilities.

7.2 - Equipment and Tools

The workshops have to fulfil the functions of maintenance and repair of a wide range of agricultural, construction, irrigation and other equipment. As this should be achieved by replacement of worn parts rather than fabrication of new items, the recommended list of tools and equipment reflects this requirement with a low emphasis on machine tools and a high emphasis on hand and special tools.

Despite the absence of crankshaft regrinding facilities and injection pump overhaul equipment there are not sufficient machines on the project to warrant the purchase of those pieces of overhaul equipment. It is recommended that the project should make use of the available facilities in Kenya, for:

(a) Crankshaft regrinding;

- (b) Recalibration of fuel metering pumps;
- (c) Repair of operators and starters.

In addition advantage should be taken of service exchange facilities, where available, for engines and hydraulic pumps. This requirement, however, should rarely be necessary within the first two years of the project and no budget costs have been allowed for that within the first two years.

The provision of additional standby units for tractors up to the level of complete engines will be part of the procurement programme.

The project will have to obtain the manufacturer's recommended tool kit required, where applicable, from the level of servicing to major repairs.

Within the project a distinction must always be made between the work to be carried out in the field and work which should be carried out in the workshop. As a general rule, if a machine needs to be dismantled for major repairs, then it should be brought back to the workshop. Field repairs are thus restricted to puncture repair, oil changes, machine adjustments and minor repairs. A small service truck is well capable of carrying out these tasks and there is no need for a fully equipped mobile workshop. The service truck should be fitted with a good mechanic's tool set, hand greasing equipment, lubricating oil, filters, etc. A 4 wheel drive pick-up has been selected for these tasks.

For fuel distribution two fuel bowsers will be required; one a 7 500 litre tanker truck for carrying fuel from the bulk storage tanks sited with the project and the other, a 5 000 litre fuel tank trailer, double axle type with drawbar, to be located adjacent to the field operations where crawler tractors are in use. The crawler tractors will run to the bowser for refuelling and the siting of the stationary bowser should keep these distances to a minimum.

The increased flexibility with wheeled machines makes possible a choice for refuelling and 40 gallon fuel drums can also be employed as a means of short term storage for isolated machines. The tanker truck would therefore be the means of distribution, either direct to machines on a daily basis or to the tractor tank or drum storage and will be kept fully occupied.

7.3 Spare Parts

As stated in Section 7.1 the project will not be able to rely upon the procurement of spare parts through a local distribution system. A high percentage of parts will have to be retained as spare parts from overseas will have a 6 to 12 month delay time between ordering and delivery.

A spares holding of 15 to 20% of the whole goods value will need to be established at project start-up. As spares are drawn down from this inventory an annual 'topping up' will be required. This will range from 3 to 5% per annum for implements and up to 10% per annum for some of the machines with fast wearing parts. This re-ordering of parts will need to commence in the second year after project start-up and will require an annual foreign exchange component of approximately US\$ 110 000 at full development from 1986 onwards. It must be emphasised that the 15 to 20% holding is not sufficient to cover operational needs for several years. As soon as parts are drawn down replacements will need to be ordered when stocks fall to specified minimum levels. The holding levels will have to be set to take procurement times into consideration.

From the proposed workshop layout it is noted that parts storage is restricted to 28 sq.m. This is very limited and it is recommended that parts and other project inputs be shipped in non-returnable containers which in turn can provide further storage space. These can be easily purchased for about US\$ 750 and these have been budgeted for in the capital costs.

CHAPTER 8

BUDGET ESTIMATES 1984 to 1986

8.1 Basis for the Estimate

The budget estimate is based on the cropping programme and farming system described in Chapter 2 and the inputs (including machinery, labour and materials) necessary to implement it successfully are specified in the succeeding chapters. The starting point for all costs is the 1984 current level. Purchases have been inflated between 1984 and 1986, at rates of between 5% and 10% per annum according to the anticipated inflation rate advised by the suppliers.

(a) Vehicles, Machinery and Equipment

The capital cost estimates are based on European and American manufacturers' prices for equipment which fits the specifications provided. Operating costs are estimated on the basis of fuel, lubricant and spare part use for an expected number of hours of operation, or in the case of transport, kilometres travelled, in each year.

(b) Irrigation

The irrigation costs refer primarily to the use of consumables, oil, lubricants and spare parts, expected to be used in producing the irrigation water requirement. Maintenance of the system (canals, drains and reservoirs) is covered under the capital and operating costs of heavy plant and equipment.

(c) Housing, Administration Buildings and Services Operation and Management

These costs include the materials necessary to maintain the buildings and Headquarters compound and the fuel, lubricants and spare parts necessary to keep the electricity generating plant operating.

(d) Salaries and Wages

These include both expatriate Technical Assistance staff and local staff (managerial, administrative, technical, skilled, semi-skilled and unskilled labour). Current Juba Sugar Company salary scales have been used as the basis for determining wage and salary levels. The levels used are essentially estimates for budgetary purposes only and are not necessarily recommended levels. It is pointed out however, that if labour is to be recruited in the Lower Juba area, the rates of pay offered will have to be competitive with the Juba Sugar Company, local banana estates and contractors. It is also suggested that the introduction of salary incentives to encourage senior executives and skilled technician staff, to commit themselves to the project, should be considered.

(e) Agricultural Inputs

The majority of these, apart from hand tools, will be imported. Fertilisers are the major cost and prices appear significantly higher than the 1983 fertiliser prices quoted by Somali Fruit, which is the major importer, whose 1983 supplies were shipped from Italy and were probably subsidised by the Italian Government. The company has indicated that it expects a considerable increase in prices this year. The prices used are based on manufacturers' current quotes and are in line with current world fertiliser prices.

(f) House and Office Furnishings

These are included in the M1 Contract and thus have already been provided for.

8.2 The Budget Estimates

Table 8.1 summarises the budget estimates for 1984 to 1986. The detailed estimates upon which the summary is based are included in Tables IV.1 to IV.16 in Appendix IV.

TABLE 8.1 Cost Estimates 1984 to 1986

TABLE 8.1 Cost Estimates 1984 to 1986

		1984			1985			1986	
Description	FE component (US\$ '000)	component (SoSh '000)	Total SoSh ('000)	FE component (US\$ '000)	Local component (SoSh '000)	Total SoSh (*000)	component (US\$ '000)	Local component (SoSh '000)	Total SoSh ('000)
	(05\$ '000)	(SOSH '000)	(1000)	(05) (00)	(3031 100)	('000)	(03\$ '000)	(2020 ,000)	('000)
L Capital costs:									
Project transport	344.38	175.63	6 030.08	- "	5. 4	9	8.50	-	3.5
Q&M plant and equipment	915.82	467.07	16 056.03					.	
Agricultural machinery Workshop & mechanical stores plant and	1 304.49	665.29	22 841.58	620.29	316.35	10 861.29			
equipment	110.29	56.25	1 931.09	-		-	•		1,00
Total capital costs	2 674.98	1 364,24	46 838,78	620,29	316.35	10 861.29	-		
10% contingency	267.50	136.42	4 683.88	62.03	31.64	1 086-13		•	-57
L Operating costs: Mogambo HG: Salaries									
and wages Workshop and mechanical stores; salaries	75.0	433.5	1 708.5	472.5	1 365.21	9 397.71	496.13	1 433.47	9 867.6
and wages Irrigation operation:	37.5	268-25	905.75	94.5	1 477.34	3 083.84	99.23	1 593.55	3 280.4
salaries and wages					404.21	404.21		634.84	634.
Field management: salaries and wages Project transport:		155.10	155.0	1.	1 031.94	1 031.94	-	1 301.83	1 301.
fuels, lubricants and spare parts			-	23.64	1 377.39	1 779.27	26.0	1 515.13	1 957.
Heavy plant: fuels, lubricants and spare parts Agricultural machinery; fuels, lubricants and	- "	•		36.51	1 174.52	1 795.19	40.16	1 291.98	1 974
spare parts Irrigation and drainage: fuels, lubricants and	0 ★			100.13	1 528.83	3 231.04	128.35	2 282.84	4 464
spare parts Agricultural labour	-	-		100	1 895.96	1 895.96	-	4 079.05	4 079.
force: wages Housing, administration	-	;:■:	*	8 3	1 248.4	1 248-4		4 602.40	4 602
buildings and			•						
services O&M	-	495.0	495.0	13.70	1 324.95	1 557.85	57.52	1 457.45	2 435.2
Agricultural inputs:				****			***		
annual costs	*			206.9	1 619.2	5 136.3	586.7	650.5	0 624
otal operating costs	112.5	1 351.75	3 264.25	947.88	16 172.94	30 561.71	1 434.09	0 843.04 4	5 222
0% contingency	11.25	135-18	326.43	94.79	1 617.29	3 056.17	143.41		4 522
Total costs and contingency	3 066.23	2 987,59	55 113,34	1 77/ 99	18 138-22	45 565,30	1 577 50	2 927.34 4	9 744

Notes: Based on Appendix IV Tables IV.1 to IV.16. Fuel and lubricants taken as local cost.

APPENDIX I

TERMS OF REFERENCE

The Consultant will carry out the work in the stages described below:

A Planning Stage (in Somali Democratic Republic and UK)

Agricultural Aspects

- Review the project construction schedule and confirm the timing of land becoming available for cultivation.
- (2) Finalise the cropping calendar and prepare a detailed schedule of field operations (timing and areas) including land preparation, planting, initial irrigation, fertilising, weed/pest control, harvesting, etc.
- (3) Design a mechanisation system and machine operation schedule on the basis of (1) and (2) above.
- (4) Identify and draw up preliminary specifications for the agricultural machinery by type and quantity taking into account the rainfall, soil conditions, field sizes, field access, and other factors to be identified during the field visit.
- (5) Examine the requirements for aerial operations such as spraying (weed and pest control) and if necessary identify the cost and source of such services.
- (6) Identify and draw up preliminary specifications for project vehicles including personnel vehicles and general transport vehicles.
- (7) Identify the support facilities (workshop, spare part stores, and fuel storage and distribution) required to maintain the fleet of agricultural machinery and project vehicles.
- (8) Determine the requirements for seed, fertiliser agrochemicals, sacking and other inputs necessary to implement the cropping programme.
- (9) Determine, skilled, semi-skilled and unskilled personnel requirements necessary to carry out all field operations, and operate, maintain and repair agricultural machinery. Prepare a detailed schedule for recruitment of personnel.
- (10) Prepare annual budgets covering capital, (machinery and transport) maintenance, repair and operation costs, personnel and agricultural input costs in detail for the first year's operation and in outline for each year to the full development of Phase 1.

Operation and Maintenance Plant and Equipment

(11) Identify and draw up preliminary specifications for the plant for the proper operation and maintenance (O/M) of the project works, including canals and roads.

- (12) Identify the support facilities (workshop bays, spare part stores and fuel storage and distribution) required to maintain the O/M plant and the irrigation pumps.
- (13) Specify workshop equipment required for the repair and maintenance of the O/M plant and the irrigation pumps.
- (14) Prepare annual budgets covering capital plant maintenance, repair and operational costs, personnel, fuel and lubricants costs in detail for the first year's operation and in outline for each year to the full development of Phase 1.

Report

THE FOOD WILLIAM

(15) Prepare Report.

APPENDIX II

DELINTING OF COTTON SEED

Where delinted cotton seed suitable for machine planting is not available, small quantities of seed, up to 3 tonnnes, can be delinted using the following method.

The equipment and materials required include:

- an old concrete mixer (driven by electric motor or internal combustion engine);
- three halves of 44 gallon drums;
- 95% pure commercial grade concentrated sulphuric acid;
- a supply of caustic soda;
- protective clothing;
- adequate supply of water.

Cotton seed and concentrated sulphuric acid in a ratio of 9 kg of cotton seed to 0.6 litre of sulphuric acid (up to 0.9 litre of sulphuric acid depending on the extent of delinting in the ginning process) are mixed for 4 to 5 minutes in the drum of the concrete mixer during which time the lint will have been burnt off and the contents of the drum form a 'sticky porridge'.

Cold water is then sprayed into the drum until the seeds are separated and the acid solution in the drum weakened. The contents of the drum are then tipped in small quantities into baskets made of mosquito netting or similar filter material. The seed is then put into the first half drum containing clean water and stirred thoroughly adding water at the same time to further dilute any remaining acid.

The seed is then removed and placed in a second drum containing 5 lb of caustic soda in solution and thoroughly mixed to neutralise any remaining acid. The seed is then removed and thoroughly washed in the third drum which is half-filled with cold water. Any floating seed is scooped off and thrown away. The remaining seed is removed and laid out in the sun to dry before bagging and storing until use.

APPENDIX III

LIST OF AGRICULTURAL EQUIPMENT AND OPERATIONS AND MAINTENANCE EQUIPMENT

The following lists show all the equipment in their proposed lots for procurement, together with the proposed phased supply.

Phase A - Nov/Dec 1984

Phase B - Nov/Dec 1985

Lot 1 - Vehicles and motor cycles

142.000		Dharada	
Item	Description	Phased s	B
1	Estate car	3	0
2	Four wheel drive station wagon	2	0
3	Four wheel drive pick-up	3	0
4	3 - 5 tonne closed van	1	0
5	10 tonne flat truck for general cargo	4	0
6	10 tonne flat truck with cargo crane	1	0
7	10 tonne tipper truck	2	0
8	7 500 I fuel tanker truck	1	0
9	Spare assemblies	1 lot	0
10	Motor cycles	12	0

	Lot 2 - Agricultural tractors, implements	and tre	ailers
Item number	Description	Phased A	supply B
1	Two wheel drive wheeled tractor	7	3
2	Four wheel drive wheeled tractor	4	3
3	Spare assemblies	1 lot	0
4	Combination grain and fertiliser seed drill	3	1
5	Spiked tooth harrow	1	0
6	Cotton/maize	1	.0
7	Fertiliser spreader	3	1
8	Inter-row cultivator	1	0
9	Rotary grass slasher	1	0
10	Cotton stalk and straw slasher	1	0
11	Front end loader equipment	4	0
12	Tine cultivator	2	0
13	5 tonne, two axle trailer	6	2
14	7 tonne grain tipping trailer	5	2
15	Water tank trailer	1	0
16	Fuel tank trailer (2 000/2 500 l)	1	0
17	Low loader trailer	1	0
18	Tractor-mounted flail unit	1	0
19	Two axle, 5 000 I fuel trailer	1	0

Lot 3 - Crawler tractors and implements

			A 602 L4 W
Item number	Description	Phased A	supply B
1	Crawler tractor	4	2
2	Bulldozer equipment	2	0
3	Land plane	2	0
4	Ploughing offset disc harrow	3	1
5	Offset disc harrow	4	2
	Lot 4 - Combine harvesters		
Item number	Description	Phased A	supply B
1	Combine harvester	5	2
	Lot 5 - Dragline excavator		
Item number	Description	Phased A	supply B
1	Dragline excavator	1	0

	Lot 6 - Workshop equipment		
Item number	Description	Phased A	supply B
1	Machine tools	l lot	0
2	Lifting frame	1	
3	Lifting slings	1 lot	. 0
4	Welding equipment	l lot	0
5	General tools and equipment	1 lot	0
6	Socket sets and spanners	1 lot	0
7	Files and drills	1 lot	0
8	Nozzle reconditioning equipment	l lot	0
9	Sawbench	1	0
10	Carpenter's tool kit	1	0
11	Plumber and pipefitter's tool kit	1	0
12	Electrician's tool kit	1	0
13	Consumables - provisional	1 lot	0
14	Handling equipment	1 lot	0
15	Store racking	1 lot	0

Lot 7 - Small items

Item number	Description	Phased A	supply B	ALC: ALC: NO.
1	Sprayer - tractor	2	1	
2	Sprayer - low ground pressure	- 1	1	
3	Knapsack sprayer	14	6	
4	Ultra low volume sprayer	45	0	
5	Rolling cultivator	1	0	- 74.74
6	Rectangular baler	1	0	
7	Grain auger	2	0	
. 8	Bag and bale elevator	1	1	- Anna
9	Elevated grain hopper	11	0	
10	Concrete mixer	1	0	
11	Water pump	1	0	
12	Bicycle	30	0	
13	Portable generator	1	0	
14	Portable tyre inflation compressor	1	0	
		THE RESERVE THE PROPERTY OF THE PARTY OF THE		

Lot 8 - Motor grader and wheeled loader

Item number	Description	Pha A	sed supply B
1	Motor grader	i	. 0
2	Wheeled loader	1	0

Lot 9 - Hydraulic backhoe excavators

Item number	Description	Phased supply A B
1	Hydraulic backhoe excavator	1 0
2	Hydraulic backhoe excavator	1 0

APPENDIX IV

DETAILED COST ESTIMATES

List of Tables :

L. Capital Costs: 1984 to 1985

Table IV.1	Capital Costs : Project Transport
Table IV.2	Capital Costs: Operation and Maintenance, Plant and
	Equipment
Table IV.3	Capital Costs: Agricultural Machinery
Table IV.4	Capital Costs: Workshop and Mechanical Stores,

2. Operating Costs: 1984 to 1986

Table IV.5	Mogambo Headquarters : Staff Salaries and Wages
Table IV.6	Workshop and Mechanical Stores: Staff Salaries and Wages
Table IV.7	Irrigation Operation: Staff Salaries and Wages
Table IV.8	Field Management: Staff Salaries and Wages
Table IV.9	Project Transport: Fuels, Lubricants and Spare Parts
Table IV.10(a)	Heavy Plant : Fuels, Lubricants and Spare Parts
Table IV.10(b)	Heavy Plant : Fuels, Lubricants and Spare Parts
Table IV.11(a)	Agricultural Machinery : Fuels, Lubricants and Spare Parts
Table IV.11(b)	Agricultural Machinery : Fuels, Lubricants and Spare Parts
Table IV.12	Irrigation and Drainage System : Fuel, Lubricants and Spare Parts
Table IV.13	Agricultural Labour Force : Wages
Table IV.14	Housing, Administration Buildings and Services : Operation and Maintenance
Table IV.15	Agricultural Inputs : Unit Costs
Table IV.16	Agricultural Inputs : Annual Costs

TABLE IV.1

Capital Costs - Project Transport

						1984	CONTRACTOR OF THE PERSON OF TH	CANADA CARACTERIA	12	1985	Total Cach	Total cost
Description	FOB unit	CF unit cost US\$	Total	Number	US\$ cost	SoSh cost	Number US\$ cost SoSh cost Total SoSh (1) cost	Number	US\$ cost	Sosh cont	Number US\$ cost SoSh cost 104si 303ni	SoSh
	000 41	14 800		•	41 400	21 114	724 914	0	0	0	•	724 914
Estate car	77 000	3			2000	750 at	483 276	0	0	0	0	483 276
4WD station wagon	12 000	13 800	7	7	77 000		ACC 704	0	0	0	0	483 276
AWD pick up	9 000	9 200	^	-	27 600	14 0/0	007 (0)			•	•	241 638
A roo was	12 000	13 800	1	1	13 800	7 038	241 638	0	•	2		
	30 000	34 500	4	4	138 000	70 380	2 416 380	0	0	0	0	2 416 280
10 ton truck					W 500	17 595	604 095	0	0	0	0	\$60 409
7500 litre fuel bowser	X0 000	3 3	4	. ;		9.000	996 686	0	0	0	0	289 966
Motor cycle	1 200	1 380	7	4	Dec et		7KB A09	c	0	0	0	768 409
Spares at 15% of capital cost					45 884	100 77						
					344 579	175 633	6 030 076		0	0	0	920 030 9

Note: (1) 3% of CIF cost covers port charges, clearance charges and transport to site.

TABLE IV.2

Capital Costs - Operation and Maintenance Plant and Equipment

					1984	•			1985	2		1
Description	FOB unit	CF unit	Total	Number	Number US\$ cost	SoSh cost	SoSh cost Total SoSh	Number	Number US\$ cost	SoSh cost	SoSh cost Total SoSh	Total cost
	cost US\$	cost US\$	number			3	cost				cost	SoSh
Dragline excevator		271 803	-	-	271 803			0	0	0	0	4 759 271
Hydraulic excevetor (mein drain)		91 713	7	-	91 713		1 605 895	0	0	0	0	1 605 895
Hydraulic excavator (distributaries)		53 360	7	7	53 360			0	0	0	0	934 334
Wheeled loader		50 05	7	-4	50 025			0	0	0	0	875 938
"rader"	123 250	141 738		-	141 738			0	0	0	0	
Low load trailer	14 500	16 675	7	н	16 675	8 504	291 979	0	0	0	0	
Flat truck with cargo crane	44 950	51 693	1	-	51 693			0	0	0	0	905 144
Tipper truck	42 050	48 358	2	7	96 716		1 693 497	0	0	0	0	1 693 497
Water tank trailer (2 000/2 500 I)		2 501	-	-	2 501	1 276	43 793	0	0	0	0	43 793
Fuel tank trailer (2 000/2 500 I)	2 175		7	-4	2 501	1 276	43 793	0	0	0	0	43 793
Flail (for tractor mounting)			7	-	8 504	4 337	148 905	0	0	0	0	
Concrete mixer	1 813	2 085	-	-	2 085	1 063		0	0	0	0	36 508
Water pump (diaphragm type)	2 610		7	-	3 002	1.531	52 565	0	0	0	0	52 565
Bicycles	116	135	2	R	4 050	2 066		0	0	0	0	
												*
Spare parts at 15% of capital cost					119 455	60 922	2 091 657					2 091 657
Total					915 821	467 070 1	070 16 036 027		0	0	0	16 036 027

:: (1) 3% of CIF cost covers port cherges, clearance charges and transport to site.

TABLE IV.3 Capital Costs - Agricultural Machinery

c herrow 12 500 19 500 19 500 19 500 11 500 11 500 11 500 12 600 2 1 750 2 2 600 2 500 2 5	20025 20025	adrra			133	roat			3	1600	
lor 35 000 11 500 19 500 19 500 10 000 10 000 11 500 11 500 11 500 21 750 2 2 600 2 500 2 500 2 500 2 500 3 500	20023200 2002320 200230 20020 200230 20	88rr a									
17 500 19 500 19 500 64 100 15 100 11 500 11 750 21 750 2 750 2 750 3 500	20022888882288888888888888888888888888	3rra		161 000			2	88 550	45 171	1 550 511	4 369 621
19 500 10 500 12 250 13 000 15 000 11 500 21 750 2 600 3 500	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	rra	7				n				
lac harrow 12 250 12 250 15 000 15 000 15 000 21 750 21 750 2 600 2 500	2002 250 880 2002 250 880 2002 250 880 2002 250 880 2002 250 880 2002 250 880 2002 250 2002 250 250 880 250 80 250 80 25	L 4	4				•				
bc harrow 12 250 15 000 15 000 11 500 11 500 2 1750 2 2 600 3 500	20025568 20025568	4	8				2				
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	2002328		•				-				
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	22 6 6 6 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6	9	4				2		16 774	575 904	
11 500 8 700 21 750 2 600 3 500	28022	2	2				0		0		
21 750 21 750 2 600 2 600 2 500	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	4	•	39 675	20 234		1		7 419		
21 750 870 2 600 3 500	2 990	3	2				-	11 006	5613	192 706	
2 600	2 9901	2	-				-		14 032		
2 200	2 990	1	7				0	0	0	0	
3 500 4	-	1	-		1 525		0	0	0	0	
	4 025	4	1		6 158		1	4 428	2 258	77 526	
4	4 025	1	-		2 053		0	0	0	0	
3 100 3	3 565	1	1		1 818		0	0	0	0	
1 300 1	1 495	1	-		762		0	0	0	0	
and strew slasher 1 300	1 495	1	-	1 495	762	26 177	0	0	0	0	26 177
	8 625	1	-		4 399		0	0	0	0	
2 250	2 588		4		5 279		0	0	0	0	
2175	2 501	2	2		2 551		0	•	0	0	
Bac and bale elevator 3 500 4	4 025	~	-		2 053		-	4 428	2 258	77 526	
3 900 4	4 485	2	2		4 575		0	0	0	0	
	5 003	a	9		5597		2	11 006	5613	192 706	
7 ton grain trailer 6 100 7	7 015	7	8		17 888		2	15 433	7 871	270 232 *	
	8 280	1	-		ಟಾವ		0	0	0		
08	104	20	14		739		9	683	348	11 961	
2	25	45	45		792		0	0	0	0	
in hopper 3 000	3 450	7	1		200		0	•	0	0	
ents 17 500	20 125	1	0.5		80 V		0.5		5 645		
ost					111 98	2 979 336	0	80 908	41 263	1 416 690	
Total				304 488	665 289	22 841 577		620 291	316 348	10 861 293	33 702 870

Notes: (1) 10% price inflation

(2) 3% CIF cost covers port charges, clearence charges and transport to site

TABLE IV.4

Capital Costs - Workshop and Mechanical Stores, Plant and Equipment

	FOB unit	CIF unit Total cost US\$ number		Number	US\$ cost	Number US\$ cost SoSh cost Tol	Total SoSh cost	Number	US\$ cost	SoSh cost	1985 Total SoSh Number US\$ cost SoSh cost Total SoSh cost	Total cost SoSh
9	059	748	9	9	4 485	2 287	78 532	0	0	0	0	78 532
90 000	0	103 500		-	103 500	52 785	1 812 285	0	0	0	0	1 812 285
2 000	0	2 300	,	1	2 300	1173	40 273	0	0	0	0	40 273
					110 285	56 245	1 931 090		0	0	0	1 931 090

Notes: (1) 3% of CIF cost covers part charges, clearance charges and transport to alte.

(2) Eatimated at US\$ 90 000.

Mogambo Headquarters - Staff Salaries and Wages

Total Calcilug Nr staff Feb 1994
1 2000 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
CS3
1 5000 1
1 5000 1 25000 2 500 1 12 500 2 500 1 12 500 550 1 12 500 1 100 0
1 3500 1 17500 1 5500 1 17500 1 5500 1 17500 1500 1 7500 650 0

Espectiste oniployment coste taken so an everage of UGS 7 300 per month. In practice there will be a differential between individual salaries according to emitriky and experience.

5% inflation allowed on all seletim per envion.

Monthly grow selecies in SuSh unions quoted otherwise. Notes (1)

⁸⁸

IV-6

TABLE IV.6

Workshop and Mechanical Stores - Staff Salaries and Wages

							100	140 1085 to Les 1085	200	1	1.4 1085 1.0 Day 1085	1000		1001	
Position	Z	Extating ataff Feb 1984	Monthly gross salery	Number	Aw 1984 to Dec 1984 er Cost SoSh Cost	1984 Cost US\$	Number	Number Cost SoSh	Cost USS	Number	Number Cost SoSh	Cost USS	Number	Cost SoSh	Cost US
Workshop steff							-		47 250	-		47 250	-		99 225
Workshop Foreman	7	_	15\$7 500	-		37 500	1	154 350		-	154 350		^	324 135	
Foreman	7		3 500	1	122 500		•	126 000		60	126 000			264 600	
Mechanics	40		2 500		100 000		10	94 500		10	94 500		10	198 450	
Mechanics II	01		1 500		0		-	15 750		1	15 750		-	33 075	
Vehicle Electricien	1		2 500		0		10	50 400		14	20 560		14	148 176	
Labourers (semi-skilled)	14		900		a		~	25 200		•	45 360		•	95 256	
Apprentices	0.		000		0		•	15 750		-	15 750		-	33 075	
Welder	-		2 500		0		7	5 040		-	5 040		-	10 584	
Welder's Assistant	-		800		0		-	15 750		7	15 750		-	33 075	
Turner	-		2 500		0		-	5 040		7	5 040		-	10 584	
Turner's Assistent	-		800		0		-	15 750		-	15 750		-	33 075	
Plumber	-		2 500		0		•	5 040		7	5 040		-	10 584	
Plumber's Assistant	-		800		0		-	15 750		-	15 750		-	33 075	
Electrician	-		2 500		0		-	5 040		7	5 040		-	10 584	
Electrician's Assistant	-		900		0		-	15 750		7	15 750		-	33 075	
Carpenter	-		200		0		-	2 040		-	5 040		-	10 584	
Carpenter's Assistant	-		000		0		•	37 600		•	37 800		•	79 380	
Truck Orivers	•		200		0		•	20 160		•	20 160		•	42.336	
Driver's Assistent	•		800		0		•	16 380		•	16 380		•	24 398	
Watchmen	•		650		0		•	16 380		•	16 380		4	24 398	
Lebourers	~		089		0										
Spare Parts Store							1	28 350		-	28 350		-	59 535	
Sanlor Storeman	-		9 800	-	22 500		-	15 750		1	15 750		-	33 675	
Spare Parts Clerk	-		2 500	-	12 500		1	9 450		-	9 450		1	19 845	
Typists	-		1 500	-	7 500		7	4 095		-	4 095		1	009 8	
L'abourera	1		059	-	3 250										
1							22	718 505	47 250	00	758 835	47 250	00	1 593 554	\$22 66
Total	3			20	268 250	37 500									

Notes: (1) Expatriate employment costs taken as an everage of US\$ 7 500 per month, in practice there will be a differential between individual solation according to seniority and experience.

(2) 5% inflation allowed on all salaries per enturn.

(3) Monthly grows selfies in 545% unless quoted otherwise.

TABLE IV.7

Irrigation Operation - Staff Salaries and Wages

In Total Evilating Haneshy Augitable to Due 1991 June 1995 to Jun																
1 5500 - 1 15700 - 1 2015.5 - 1 2 2500 - 1 15700 - 2 33035 - 2 8 1300 - 4 27720 - 4 4559 - 8 14 1300 - 6 41500 - 10 7275 - 10 20 6501 - 6 41500 - 10 7275 - 20 20 204.20	Position	Total	Existing real		Aug 18	at SoSh C	11	. Number	See Soth	One USS	Named	Cost SoSh	Cost LSS	Number	1986 Cost SoSh	Cost USS
intents 2 2.500 - 1 2.050 - 1 20152.5 - 1 and the state of the state o	Operation and Maintenance Staff															
intenta 2 2500 1 15750 - 2 35075 - 2 mm 1 1100 - 6 41560 - 10 72750 - 10 72750 - 10 14 1100 - 6 41560 - 10 7275	Surveyor	1		3 500				-	22 050			23 152.5		1	48 620	•
ma, 14 1100 - 4 27720 - 6 43.659 - 8 14 1100 - 6 41,500 - 10 77.963 - 34 20 650 - 10 40.950 - 14 60.196,5 - 20	Survey Assistanta	7		2 500	4			-	15 730		~	33 075		~	69 637	•
Alders, 14 1.100 . 650 . 10 72.765 . 14 1.50 . 10 72.765 . 14 1.50 . 15 1.50 . 15 1.50 . 20 1.50	Operators	•		1 100				•	27 720		•	43 639			122 245	
rerr • 20 650 - 10 40 950 - 14 60 196.5 - 20	Ditch Riders ,	=		3.100	•			•	41 580		9	72 765		2	626 572	*
827 822 004 627	Labourers ·	2		: 059			100	91	40 950	•	4	60 196.5		8	180 569	•
	Total			1		į			129 780			274 428	ないのでは		634 840	

Note : (1) 5% inflation allowed on all selectes per annum.

TABLE IV.8

Field Management - Staff Salaries and Wages

Total	Existing staff Feb 1984	Monthly gross salary	Aug Number	Aug 1984 to Dec 1984 Number Cost SoSh Cost US\$	Jan 15 Number	Jan 1985 to Jun 1985 nber Cost SoSh Co	BS Cost US\$	Jul 1985 to De Number Cost SoSh	Jul 1985 to Dec 1985 er Cost SoSh Cos	1785 Cost US\$	Number	1986 Cost SoSh	Cost US\$
		3 000 1 500 1 200			ичи	37 800 37 800 37 800		200	807 % 007 % 008 £7		4 7 7	158 760 138 915 238 140	
								9					
	×	1 400 1 100 800	1211	7 000 60 500 48 000	1 16 17	8 820 110 880 85 680		16	8 820 110 880 85 680		179	18 522 232 848 179 928	
		1,400 1,100 800	404	7 000 16 500 16 000	~~~	8 820 34 650 30 240		400	6 820 34 650 30 240		46.4	18 522 72 765 63 504	
		1 400 1 100 800		000	192	8 820 41 580 35 280		1 6	8 820 41 580 35 280		196	18 522 87 318 74 088	
			32	155 000	и	478 170		2	553 770		98	1 301 832	

Note: (1) 5% inflation allowed on all salaries per annum.

Project Transport: Fuel, Lubricants and Spare Parts

Total	use fuel cost insurance year per year (1) SoSh	714	229 861 457 503	Total Total Tax & fuel use fuel cost Insurance per year (1) 5oSh	200 200 200 200 200 200 200 200 200 200	229 947 603 554
	use/year/ fuel use machine per year	257 256 256 257 257 257 257 257 257 257 257 257 257	158.2	Fuel Tota use/year/ fuel machine per	288888 3388888 3388834	*
	use use/ lem/litre mec	6 8 8 8 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		Fuel F use use km/litre ma	8888888	
1.5	58	222222	12 054	SoSh cost	22593E3	10 239
200	Spere to Control	22 1 6 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	20.03	USS CIF cost spare parts	20 4 1 B 1 5 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	2 998
	spart US\$	22.886.886.886.886.886.886.886.886.886.8	20 552	Total FOB cost US\$ spare parts	2282282 2282282 2282282 2282282 2282282 228228	22 607
	Maintenance cost/vehicle US\$/year	883388*		Maintenance cost/vehicle US\$/year	12122	
Appellion of the Control of the Cont	Annual maintenance	@r@@r4@		Annual maintenance	araar40	
	Maintenance % cap.cost	5333333		Maintenance % cap.cost	3333333	
	Vehicle life (yrs)	vavvadv		Vehicle 'Hro (yrs)	vavada	
	Annual (km)	8888888		Annual (km)	8888888	
	Vehicle life (km)	8888888		Vehicle life (km)	8888888	
	Number of vehicles	^^*-		Number of vehicles	nn	
	Fuel cost per litre	3333333		Fuel cost per litre	333333	
	Capital cost (FOB) US\$	250 250 250 250 250 250 250 250 250 250		Capital cost (FOB) USS	229222	
(a) Year 1985	Description	Estate cer 4 wheel drive station wagon 4 wheel drive pick-up 3 ton van 10 ton truck 7 500 litte fuel bowser Motor cycle	Totals	(b) Year 1966 Description	e station wagor e pick-up uel bowser	Motor cycse

IV-10

^{10%} of capital cost per vehicle per year. Notes: (1)

Rate of exchange used 1 US\$ = 17.0 SoSh. 8 8

^{10%} inflation per annum allowed for fuel costs.

Heavy Plant: Fuel, Lubricants and Spare Parts

Total lubrication cost SoShiyear (4)	14 650 9 035 6 620 11 000 10 560 10 560 10 560 10 57 10 50 10 50 1	16 335 9 982 7 260 11 100 11 616 16 616 76 76 76 76
Total fuel cost SoShlyser	146 500 70 750 70 750 110 000 110 000 100 600 100 600	163 339 77 6605 112 000 116 160 754 754 667
Total fuel use litres/yaar	22 25 26 26 26 26 26 26 26 26 26 26 26 26 26	22288 22288 223888888888888888888888888
Fuel use/year/ machine (litres)	15 500 17 500 19 200 19 200 19 200 12 54 12 54	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Fuel use/hour Olitres)	822 - 222 -	22 - 22 - 22 - 22 - 22 - 22 - 22 - 22
Local SoSh coat	4 159 1 811 2 001 2 001 2 001 7 001 106 1106 112 901	2 205 2 205 2 205 3 180 477 417 65 11 25 11 25
Total CIF cost US\$ spare perts	8 155 5 668 4 002 5 670 5 670 2 811 2 20 151 2 5 374	8 970 2 4 905 4 4 905 5 256 2 256 2 256 2 256 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Yotal FOB cost US\$ spare perts	2 190 2 190 2 2 20 3 480 3 490 191 191 191 191	2 X09 2 X09 2 X09 3 X22 3 X23 5 423 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Spare parts cost/ machina	7 091 2 190 2 200 2 200 5 460 7 460 181 181	5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
Spare parts genuel use		~~~~~~~
Spare parts % csp.cost	X3333X3X	2333323
Machina (gra)	2200202	22 24 24 4 2
Annual	888888	8888888
Machine life (h)	88888888	88888888
Engine	22 B 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	32683522
Number of machines		
Fuel cost.	22222522	99999499
Capital cost (FOB) US\$	25, 356 46, 506 41, 500 112) 250 7, 355 1 1 815 2 610	25, 25, 25, 25, 25, 25, 25, 25, 25, 25,
Description	1965 Chapline Hydraulic excavator Hydraulic excavator Minerled loader Crader Fiall Concrete mixer Water pump	1966 Dragine Hydraulic excavator Hydraulic excavator Hydraulic excavator Creder Creder Final Final Final Final Totals

Maximum life of any machine, regardless of hours completed, has been taken as 10 years. Notes : (1)

FOB cost increased by 15% to obtain CIF.

Local coats on assumed 7% of CLF cost in SoSh.

Lubrication cost assumed 10% of fuel cost. 2 3 3 3

Rate of exchange US\$ 1 = 505h 17.0.

Heavy Plant: Fuel, Lubricants and Spare Parts

Low load trailer Flat truck (cargo crave) Tipper truck Water tank trailer (2 500 t) Frue tank trailer (2 500 t) Bicycles Totals Low load trailer Flat truck (cargo crave)	Capital Capita	18	10 1 10 1	Vehicle (m)]13 .88]13 .81	ATE Second ATE Second	Maintenance & cop.com.	1	CSEL/periodicia Control Contro	Total Total Control of the Party of the Part	Bills ASERBR A Bills XXX	20 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	11	1 188555 1 1 588 88	11 488555 8 111 8885 11 588555 8 111 588	the sum of the same	20 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Tipper truck Water tank trailer (2 500 i) Fuel tank trailer (2 500 i) Bicycles Totals	*****	9:55	N-12	8	∄ · · · R				NA.	S Exx	895 %	XX3 X	11 1	111	8 44 8	9	8 35

Assumed 10% of capital cost (FOB) per vehicle per year expressed in 509h.

Rate of exchange USS 1 = SeSh 17.8.

Local costs on sewmed 7% of Ciff cost in SoSh.

FOB cost increased by 1% to obtain CF.

Lubrication cost assumed 10% of fuel cost.

3

8 8

IV-12

Agricultural Machinery: Fuel, Lubricants and Spare Parts - Year 1985

loo la	\$ 6000000000000000000000000000000000000
Total Inferication cost SoSN/year	2828 3
Total fuel cost SoSN/year	418 698.0 222 552.0 222 552.0 302 362.5 8 167.5 1 980 1 980 1 983 417
Total fuel use litres/year	24 258
Fuel use/year/ machine (Ittres)	1 485
Feet Marca)	8888
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2002 1 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Total CIF cost USS spera perts	126882125882125882532588258258258258258258258258258258258258
Total FOB cost US\$ spare perts	# 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Spare parts cost/ machine per year	25.25.25.25.25.25.25.25.25.25.25.25.25.2
Spare parts ernual use	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
Spare parts % cep.cost	
Mechine (979)	~~~~ 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
See al	55555555555555555555555555555555555555
Machina IIfe (h)	\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Englis To	888255555555555555555555555555555555555
Number of machines	************************
Fuel coet SoSh/litre	\$
Capital cost (FOB) USS	* 11 2 2 11 21 2 2 2 2 2 2 2 2 2 2 2 2 2
Description	90 hp crawler tractor 75 hp 2 wheel drive tractor 75 hp 4 wheel drive tractor 75 hp 4 wheel drive tractor 75 hp 4 wheel drive tractor 76 first disc harrow Coffrat disc harrow Coffrat disc harrow Cotton planter Fertiliser spreader Inter-row cultivator Reling cultivator Reling cultivator Cotton etaik & straw slasher Rectangular baler Front end landers Grain, bag & bale elevator Tine cultivator A wheel 5 ton trailer 7 ton grain trailer 7 ton grain trailer Trailed fuel bowser Knappack aprayer CLA ygrayer (2) Elevated grain hopper Miscellaneous implements Workshop consumables

Notes 1 (1) Maximum Ilfe of any machine, regardless of hours completed, has been taken as 10 years.

⁽²⁾ Includes the cost of batteries in the spare parts cost.

Agricultural Machinery: Fuel, Lubricants and Spare Parts - Year 1986

90 to creater tractor 55 to 2 wheel drive tractor 55 to 2 wheel drive tractor 55 to 2 wheel drive tractor 55 to 3	. 5	12	138	a capacia			10 10 10 10 10 10 10 10 10 10 10 10 10 1	200	28 g			Total feel two literal/year	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Lidentication cont SoSN/year
See der herror 1220 P. P	Heev		brus	2222		ESES	2252	9868	2268	8888 8888 8888	3256	X S E S X	200 MAS 200 MA	6222 6222
######################################	2047	7	2225	2225	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	3888		2986		0000	0000	0000	0000	
tivator tivator tivator tivator bale trailer	MAN		1-22	2222	000	168*1	A STATE OF THE PARTY OF THE PAR	9338	33.,	0800	200	2 900	2 3 3 4 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	-8
A stress alsoher 1 X0 As baller 2 X0 As baller 2 X0 As baller 2 X0 As balle alevator 2 X0 As baller 2 X0 As bal	•		17887	*****	nnng	E222	SSSS	*****	3028				0000	
888888 888888 888888 888888 888888 88888	NN 800		A	22222	lasunu	ឧទ្តកនទ	2 2 K K K	* 25 2 3 E	s K z J z	2000	22008			
opper 3 000 n/o 1 mobiles 17 500 n/o 1 mobiles 70 000 n/o 1		255889965 222 88888888	nandunus '	RRRRRRR,	vangddaa	38ecc=-638	8666k288¥	3260330EE	edeaderes 2					
							III 622	W 82	20 80			93.3%	2 015 802	100

⁽¹⁾ Maximum life of any machine, regardless of hours completed, has been taken as 30 years.
(2) Includes the cost of batteries in the spars parts cost.

TABLE IV.12

Irrigation and Drainage System

Fuel, Lubricants and Spares

Total Iubrication cost SoSh/year	276 422	84 491	9 910	370 823
1986 Fuel use/year litres	456 895	139 655	16 380	612 930
Total fuel cost SoSh/year	2 764 220	. 844 913	660 66	3 708 231
Total Iubrication cost SoSh/year	110 951	57 490	3 919	172 360
1985 Fuel use/year litres	201 729	104 526	7 126	313 381
Total fuel cost SoSh/year	1 109 508	574 898	39 196	1 723 602
Description	Main irrigation pump station	Sprinkler pump station	Drainage pump station	Totals

- Figures taken from Chapter 4 of the Report. Notes: (1)
- (2) Lubricants assumed at 10% of fuel costs.
- (3) Spares costs nil in 1985 and 1986.

TABLE IV-13
Farm Unskilled Labour : Wages Cost(1)

	1985(2)	1986(3)
Regular labour : Surface irrigation area Sprinkler irrigation area	782.0 68.0	1 687.4 174.0
Sub-total	850.0	2 711.4
Casual labour : Surface irrigation area Sprinkler irrigation area	52.0 3.8	79.2 5.7
Sub-total	55.8	84.9
Cotton pickers	30.6	168.1
Bird scarers(4)	312.0	1 638.0
Total	1 248.4	4 602.4

- Notes: (1) Based on estimate of labour requirements. Table 5.1 (Chapter 5).
 - (2) 1985 wage notes: regular labour and cotton pickers 5oSh 680 per month; casual labour SoSh 20 per day; bird scarers SoSh 300 per month.
 - (3) 1986 wage rates : regular labour and cotton pickers SoSh 680 per month; casual labour SoSh 22 per day; bird scarers SoSh 350 per month.
 - (4) The number of bird scarers required will be slightly variable from year to year but some budget provision must be made to cover costs if they are required.

TABLE IV.14

Housing, Administration Buildings and Services

Operation and Maintenance

98	Local	ent component (SoSh)		1 324 950	132 495	1 457 445
	H	(\$SD)	57 520	ŗ	·	57 520
	Local	(SoSh)	r	1 204 500	120 450	1 324 950
19	FE	component (US\$)	13 695	ŗ	<u>,</u>	13 695
	Local	(US\$) (SoSh)	ī	450 000	45 000	495 000
1984	FI FI	component (US\$)	1	1	,	1
Description			Materials and spares	Fuel costs	Lubrication costs	Total

Note: (1) Figures taken from Chapter 4 of the Report.

TABLE IV-15
Agricultural Inputs : Unit Costs 1985/86

		1985			1986	
	FE component US\$	Local component SoSh	Total(1) SoSh	FE component US\$	Local component SoSh	Total SoSh
Seed: Rice(per kg) Cotton		7.0 Supp	7.0 plied free o	f charge by S	7.5 omaltex	7.5
Fertiliser:(2) Urea (per tonne) DAP (per tonne)	245 355	250 250	4 415 6 785	260 380	300 300	4 720 6 760
Agri-chemicals:(3) Stam F34 (per litre) Avirosan (per litre) 2,4D amine (per litre) Treflan (per litre) Cotoran (per litre) Codol (per litre) Nuvacron (per litre) Fernasan D (per kg)	3.5 12.3 3.0 6.5 7.4 8.4 6.4 3.5	3.0 10.0 10.0 6.0 10.0 10.0 6.0	62.5 220.0 60.0 115.0 135.0 155.0 120.0 65.0	3.9 13.6 3.3 7.2 8.0 9.2 7.0 3.8	4.0 12.0 12.0 7.0 12.0 12.0 12.0	70.0 245.0 70.0 130.0 148.0 170.0 132.0 70.0
Protective clothing Sacks (per 100)	30 85	75	510 1 520	35 95	80	595 1 695
Hand tools: Spades (each) Jambis (each) Pangas (each)	:	-	210 120 250	-		230 130 275
Sulphuric acid (litre)	1.0	10.0	27	1.1	12	30.
Infield works: Siphon tubing Portable canvas unit	17.25	8.87	302.0	18,11	9.24	317
Channel checks	595	303.5	10 418	624.7	319	10 940

Notes: (1) Exchange rate US\$ 1 = SoSh 17.0

⁽²⁾ Urea bagged in Europe - shipped to Mogadishu; DAP ex-Gulf bagged in Europe and shipped to Mogadishu. Prices are considerably higher than current prices quoted by Somali Fruit. Somali Fruit however (personal communication anticipate considerable increases in fertiliser prices in 1984 and 1985.

⁽³⁾ Prices ex-Europe but based on current quotations C and F Mogadishi increased by 10% per annum price inflation.

TABLE IV.16

Agricultural Inputs : Annual Cost Estimate 1985/86

	1985				1986		
	FE component (US\$ '000)	Local componen (SoSh '000		FE component (US\$ '000)	Local component (SoSh '000)	Total (SoSh) ('000)	
Seed: Rice	•	1 365.0	1 365.0	×	-		
Fertiliser urea DAP	37.0 39.6	37.8 27.9	6 66.7 700.8	207.5 94.2	239.4 74.4	3 766.6 1 676.5	
Agri-chemicals: Stam F34 Avirosan 2,4D amine Treflan Cotoran Codol Nuvacron Fernasan D Protective clothing Sacks	57.1 12.3 0.06 2.3 0.2 0.3 17.6 1.6	48.9 10.0 0.2 2.1 0.3 0.3 27.5 2.7	1 018.8 220.0 1.2 40.3 3.4 4.7 330.0 29.3 25.5	144.3 13.6 0.07 3.3 0.2 0.3 25.7 2.2	148.0 12.0 0.24 3.2 3.0 0.4 44.0 4.1	2 590.0 245.0 1.4 59.8 3.7 5.1 484.4 40.6	
Hand tools: Spades Jambis Pangas		23.1 13.2 27.5	23.1 13.2 27.5	:	16.1 9.1 19.3	16.1 9.1 19.3	
Sulphuric acid	0.4	4.0	10.8	0.6	6.0	15.0	
Infield works: Siphon tubing Portable canvas unit Channel checks	7.9 2.4	4.0 1.2	138.7 41.5	19.5 5.7	10 . 0	342.6 100.3	
Total	206.9	1 619.2	5 136.3	586.7	650.5	10 612.9	